



CUSTOMER TERMINAL	RoHS	LEAD(Pb)-FREE
Sn96%, Ag4%	Yes	Yes



ELECTRICAL SPECIFICATIONS @ 25°C unless otherwise noted:

PARAMETER	TEST CONDITIONS	VALUE
D.C. RESISTANCE	1-4 @20°C	0.560 ohms max.
D.C. RESISTANCE	8-5 @20°C	0.560 ohms max.
INDUCTANCE	4-1 50kHz, 10mVAC, Ls	260uH ±15%
LEAKAGE INDUCTANCE	4-1 tie(5+8), 100kHz, 10mVAC, Ls	8uH max.
DIELECTRIC	4-8 1750VAC, 1 second	-
URNS RATIO	(4-1):(8-5)	1:1, ±2%



GENERAL SPECIFICATIONS:

OPERATING TEMPERATURE RANGE: -40°C to +125°C including temp rise.

Wire insulation & RoHS status not affected by wire color.
Wire insulation color may vary depending on availability.

REV.	DATE	Packaging Specifications Method: Tape & Reel PKG-0193 www.we-online.com/midcom		Tolerances unless otherwise specified: Angles: ±1° Fractions: ±1/64 Decimals: ±.005 [.13] Footprint: ±.005 [.13]	DRAWING TITLE TRANSFORMER	PART NO. 750342304
6A	8/14	SEE REVISION SHEET FOR REVISION LEVEL	CONVENTION PLACEMENT	This drawing is dual dimensioned. Dimensions in brackets are in millimeters.	eiSos p/n: 750342304	SPECIFICATION SHEET 1 OF 1