

**Features**


- Low Phase Noise
- Wide Temperature Range
- SMD Package (7.0x5.0mm)

**Applications**

- Base Stations
- Instrumentations
- Synthesizer
- SDH/SONET
- Medical Electronics


**BT0507E Specifications**

Parameter	Value			Unit	Conditions	
	Min.	Typ.	Max.			
Supply Voltage	-	3.3	-	V		
	-	5	-	V		
Supply Current	3	-	8	mA		
Frequency Range	10 ~ 52			MHz		
Nominal Frequency	10, 12.8, 13, 15.36, 16, 16.32, 16.384, 19.2, 19.44, 20, 24.576, 25, 26, 30.72, 38.4, 38.88, 40, 50			MHz		
Initial Frequency Tolerance	±0.05	-	±0.5	ppm	At shipment, nominal EFC, +25°C	
Freq. Stability Vs. Temp.	±0.05	-	±0.5	ppm	-20°C ~ +70°C	
	±0.05	-	±0.5	ppm	-40°C ~ +85°C	
	±0.2	-	±1.0	ppm	-50°C ~ +90°C	
	±0.5	-	±1.0	ppm	-55°C ~ +95°C	
Clipped Sine Wave	Output Level	0.8	-	Vp-p		
	Load	10kΩ//10pF				
CMOS	V <sub>OH</sub>	2.4	-	V	LVC MOS Output, Load=15pf	
	V <sub>OL</sub>	-	-	0.4	V	LVC MOS Output, Load=15pf
	Duty Cycle	45	-	55	%	(V <sub>OH</sub> - V <sub>OL</sub> )/2
	Rise/Fall Edge	-	-	6	ns	LVC MOS Output, Load=15pf
	Load	-	-	15	pf	
RMS Jitter(By E5052B)	0.4	-	1.3	ps	12KHz~5MHz	
Supply Sensitivity	-	-	±0.1	ppm	V <sub>CC</sub> ±5%	
Load Sensitivity	-	-	±0.2		Load±5%	
Aging/ First Year	-	-	±1.0		Standard	
	±0.3	-	±0.8		Customized	
SSB Phase Noise @10MHz	-	-	-105	dBc/Hz	Offset 10Hz	
	-	-	-130		Offset 100Hz	
	-	-	-150		Offset 1kHz	
	-	-	-155		Offset 10kHz	
	-	-	-158		Offset 100kHz	
Control Voltage Range	1.5 ± 1.0			V		
Frequency Turning Range	±5	-	±12	ppm		
Tuning Slope	positive					
Non-linearity	-	-	10	%		
<b>Phase Noise @1KHz</b>						
Freq. Range	<-140dBc	<-145dBc	<-147dBc	<-150dBc	○=Available X=Not Available	
10MHz				○		
12.8~20MHz			○	X		
20.48~40MHz		○	X	X		
50MHz	○	X	X	X		

Environmental Conditions													
Operating Temperature Range	-55°C ~ +95°C												
Storage Temperature Range	-55°C ~ +125°C												
Outline Dimension & Pin Connections													
													
<table border="1" style="margin-left: auto; margin-right: auto;"> <caption>Pin Connections</caption> <tr><td>Pin1</td><td>Vcon/NC</td></tr> <tr><td>Pin2</td><td>*</td></tr> <tr><td>Pin3</td><td>GND</td></tr> <tr><td>Pin4</td><td>Output</td></tr> <tr><td>Pin5</td><td>*</td></tr> <tr><td>Pin6</td><td>Vcc</td></tr> </table>		Pin1	Vcon/NC	Pin2	*	Pin3	GND	Pin4	Output	Pin5	*	Pin6	Vcc
Pin1	Vcon/NC												
Pin2	*												
Pin3	GND												
Pin4	Output												
Pin5	*												
Pin6	Vcc												
<p><b>Note:</b></p> <ol style="list-style-type: none"> <li>The pins with "*" are for factory test.</li> <li>Leave pin 1 unconnected if Vcon is not used.</li> </ol>													
Maximum Ratings													
<b>Parameter</b>	<b>Symbol</b>	<b>Rating</b>											
Supply Voltage	Vdd	-0.5V / 6V											
Control Voltage	Vcon	0V / 3V											
ESD, HBM/CDM/MM		4KV/ 2KV/ 200V											
Reliability													
<b>Parameter</b>	<b>Condition</b>												
Temperature Stress Test	IEC60068, GJB360B												
Mechanical Stress Test	IEC60068, GJB360B												
EMC Test (ESD)	IEC61000, JESD22												
Solderability	EIA/JESD22-B102-C												
Contact Pads	Gold over Nickel												
RoHS	RoHS Directive 2011/65/EU Annex II Recasting 2002/95/EC												
Ordering Guide													
BT 0507 X X X X XXX X X XX.XX													
<table border="1" style="width: 100%;"> <tr><td>Product: TCXO</td></tr> <tr><td>Outline: 7.0mm x 5.0mm</td></tr> <tr><td>Package: E: Package E</td></tr> <tr><td>Output: H: LVCMOS C: Clipped Sine Wave</td></tr> <tr><td>Supply Voltage: 3: 3.3 Vdc 5: 5.0 Vdc</td></tr> <tr><td>Temp. Range: C: -20°C ~ +70°C I: -40°C ~ +85°C M: -50°C ~ +90°C U: -55°C ~ +95°C F: Customized</td></tr> </table>	Product: TCXO	Outline: 7.0mm x 5.0mm	Package: E: Package E	Output: H: LVCMOS C: Clipped Sine Wave	Supply Voltage: 3: 3.3 Vdc 5: 5.0 Vdc	Temp. Range: C: -20°C ~ +70°C I: -40°C ~ +85°C M: -50°C ~ +90°C U: -55°C ~ +95°C F: Customized	<table border="1" style="width: 100%;"> <tr><td>Frequency: xx MHz</td></tr> <tr><td>Tuning Range: N: No Tuning A: ±5ppm B: ±7ppm C: ±12ppm</td></tr> <tr><td>Phase Noise: D: -135dBc/Hz@1kHz E: -140dBc/Hz@1kHz G: -145dBc/Hz@1kHz</td></tr> <tr><td>Temp. Stability: 507: ±0.5ppm 207: ±0.2ppm 107: ±0.1ppm 508: ±0.05ppm</td></tr> </table>	Frequency: xx MHz	Tuning Range: N: No Tuning A: ±5ppm B: ±7ppm C: ±12ppm	Phase Noise: D: -135dBc/Hz@1kHz E: -140dBc/Hz@1kHz G: -145dBc/Hz@1kHz	Temp. Stability: 507: ±0.5ppm 207: ±0.2ppm 107: ±0.1ppm 508: ±0.05ppm		
Product: TCXO													
Outline: 7.0mm x 5.0mm													
Package: E: Package E													
Output: H: LVCMOS C: Clipped Sine Wave													
Supply Voltage: 3: 3.3 Vdc 5: 5.0 Vdc													
Temp. Range: C: -20°C ~ +70°C I: -40°C ~ +85°C M: -50°C ~ +90°C U: -55°C ~ +95°C F: Customized													
Frequency: xx MHz													
Tuning Range: N: No Tuning A: ±5ppm B: ±7ppm C: ±12ppm													
Phase Noise: D: -135dBc/Hz@1kHz E: -140dBc/Hz@1kHz G: -145dBc/Hz@1kHz													
Temp. Stability: 507: ±0.5ppm 207: ±0.2ppm 107: ±0.1ppm 508: ±0.05ppm													
<p><b>Example:</b> BT0507EH3I207EN40</p>													