


NOTES:

1. METALSHELLS: STEEL; min. 315µin TIN over 40-80µin NICKEL
2. INSULATORS: PBT GF UL 94 V-0, BLACK
3. CONTACTS: COPPER ALLOY; PLATING (SEE PART NO.):
 - PLEASE ADD A for GOLD FLASH over NICKEL (PREFERRED TYPE)
 - PLEASE ADD B for 20µin HARD GOLD over min. 50µin NICKEL
 - PLEASE ADD C for 30µin HARD GOLD over min. 50µin NICKEL
4. METAL BRACKETS: ZINC DIE CAST; 300µin COPPER/40-120µin NICKEL/120-200µin TIN
5. THREADED INSERTS: COPPER ALLOY; min. 200µin TIN over 80µin NICKEL
6. FIXING PLATE: PBT GF UL 94 V-0, BLACK
7. P.C.B. HOLE DRILLINGS SEE SHEET 2
8. MAXIMUM TORQUE VALUE FOR THREAD: 6 in.LB
9. CONNECTOR IS PART MARKED: **163□15579X CONEC ABC**

Directive 2002/95/EC RoHS compliant

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH DO NOT ALTER CAD DRAWING BY HAND				tolerance		dim. in mm	scale: 2:1		
				material: SEE NOTES					
				date	name	title: D-SUB DUAL PORT 19,05mm			
				drawn	08.08.11	Henneboel	25pos.Male / 25pos. Female		
				appd.	09.08.11	Fischer	with threaded insert		
				norm			dwg no:		
				d-old			16K1A2853		
				2 x b	A5247	16.06.2014	K.H.	DIN-A3	
				a	Original			sh: 1/2	
				rev.	description	date	name	part no: (b) 163□15579X (see note 3)	
				CONEC					

P.C.B. HOLE DRILLINGS
(P.C.B. TOP SIDE)



THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH DO NOT ALTER CAD DRAWING BY HAND				tolerance		scale: 2:1	
				date	name	material: SEE SHEET 1	
				drawn	08.08.11	Henneboel	title: P.C.B. HOLE DRILLINGS DUAL PORT 19,05mm 25pos. MALE / 25pos. FEMALE with threaded insert
				appd.	09.08.11	Fischer	
				norm			
				d-old			dwg no:
	a	Original		CONEC [®]			16K1A2853
rev.	description	date	name				part no: SEE SHEET 1