

# Data Sheet

## 2SB315A-2MBI800VT-170E

### SCALE Dual-Channel Plug-and-Play Driver

Driver solution for 130mm x 140mm dual IGBT modules with electrical interface for 2-level topologies

#### Abstract

The 2SB315A-2MBI800VT-170E is a dual-channel driver with an electrical interface based on CONCEPT's dual SCALE driver 2SD315AI, a proven technology for reliable driving and safe operation of IGBTs.

The driver is matched to the 1700V module 2MBI800VT-170E from Fuji. Its plug-and-play capability makes it ready to operate immediately after mounting. The user needs invest no effort in designing or adjusting it to a specific application.

For drivers adapted to other types of high-power and high-voltage IGBT modules, refer to [www.IGBT-Driver.com/go/plug-and-play](http://www.IGBT-Driver.com/go/plug-and-play)

#### Product Highlights

- ✓ Suitable for 2MBI800VT-170E
- ✓ Plug-and-play solution
- ✓ Active clamping of  $V_{ce}$  at turn-off
- ✓ IGBT short-circuit and overcurrent protection
- ✓ No electrolytic capacitors
- ✓ 20-pin flat cable interface
- ✓ Monitoring of power supply voltage
- ✓ Duty cycle 0... 100%
- ✓ Extremely reliable; long service life
- ✓ Shortens application development time

#### Applications

- ✓ Inverters
- ✓ Motor drives
- ✓ UPS
- ✓ Power-factor correctors
- ✓ Wind-power converters
- ✓ Welding
- ✓ SMPS
- ✓ and many others

## Data Sheet 2SB315A-2MBI800VT-170E

Important: Please refer to the relevant manuals!

This data sheet contains only product-specific data. A detailed description, must-read application notes and general data applicable to this driver family are found in: "Description and Application Manual for 2SB315A SCALE Plug-and-play IGBT Driver".

See [www.IGBT-Driver.com/go/2SB315A](http://www.IGBT-Driver.com/go/2SB315A)

### Dimensions

Dimensions: 130 x 145 mm, 21 mm height (30 mm with connector X1 and flat cable).

Mounting principle: Connected to IGBT module with screws.

### Absolute Maximum Ratings

| Parameter                       | Remarks             | Min | Max      | Units |
|---------------------------------|---------------------|-----|----------|-------|
| Supply voltage $V_{DC}$         | VDC to GND (Note 1) | 0   | 16       | V     |
| Supply voltage $V_{DD}$         | VDD to GND          | 0   | 16       | V     |
| Logic input voltage             | To GND              | 0   | $V_{DD}$ | V     |
| Gate peak current $I_{out}$     | Note 6              | -15 | +15      | A     |
| Average supply current $I_{DC}$ | Notes 2,3           |     | 500      | mA    |
| Output power per gate           | Note 3              |     | 3        | W     |
| Switching frequency             | Note 3              |     | 8        | kHz   |
| DC-link voltage                 | Note 4              |     | 1200     | V     |
| Operating temperature           | Note 3              | -40 | +85      | °C    |
| Storage temperature             |                     | -40 | +90      | °C    |

All data refer to +25°C and  $V_{DC} = 15V$  unless otherwise specified

### Electrical Characteristics

| Power supply                        | Remarks                      | Min | Typ. | Max      | Units           |
|-------------------------------------|------------------------------|-----|------|----------|-----------------|
| Nominal supply voltage $V_{DC}$     | To GND (Note 1)              |     | 15   |          | V <sub>dc</sub> |
| Supply current $I_{DC}$             | Without load                 |     | 80   |          | mA              |
| Supply current $I_{DC}$             | At 8 kHz switching frequency |     | 500  |          | mA              |
| Efficiency $\eta$                   | Internal DC/DC converter     |     | 85   |          | %               |
| Nominal supply voltage $V_{DD}$     | To GND                       |     | 15   |          | V <sub>dc</sub> |
| Supply current $I_{DD}$             | Without load                 |     | 10   |          | mA              |
| Supply current $I_{DD}$             | At 8 kHz switching frequency |     | 12   |          | mA              |
| Power supply monitoring             | Test conditions              | Min | Typ. | Max      | Units           |
| Turn-on threshold $V_{th}$          | Note 5                       |     | 10.6 |          | V <sub>dc</sub> |
| Hysteresis on/off                   | Note 5                       |     | 0.6  |          | V <sub>dc</sub> |
| Short circuit protection            | Remarks                      | Min | Typ. | Max      | units           |
| $V_{ce}$ -monitoring threshold      | Betw. aux. terminals         |     | 6.3  |          | V               |
| Response time                       | Note 7                       |     | 10.8 |          | $\mu$ s         |
| Blocking time                       | After failure (Note 8)       |     | 1    |          | s               |
| Logic inputs                        | Test conditions              | Min | Typ. | Max      | Units           |
| Input voltage                       | All inputs                   | 0   |      | $V_{DD}$ | V <sub>dc</sub> |
| Timing characteristics              | Test conditions              | Min | Typ. | Max      | Units           |
| Turn-on delay $t_{pd(on)}$          | Note 9                       |     | 400  |          | ns              |
| Turn-off delay $t_{pd(off)}$        | Note 9                       |     | 500  |          | ns              |
| Output rise time $t_{r(out)}$       | Gx to Ex (Note 10)           |     | 150  |          | ns              |
| Output fall time $t_{f(out)}$       | Gx to Ex (Note 10)           |     | 80   |          | ns              |
| Dead time between outputs           | Half-bridge mode             |     | 2.5  |          | $\mu$ s         |
| Outputs                             | Test conditions              | Min | Typ. | Max      | Units           |
| Turn-on gate resistor $R_{g(on)}$   |                              |     | 1.5  |          | $\Omega$        |
| Turn-off gate resistor $R_{g(off)}$ |                              |     | 9.1  |          | $\Omega$        |
| Output current SOx                  |                              | 1.5 |      |          | mA              |
| Output voltage rating SOx           | SOx to GND                   |     |      | $V_{DD}$ | V               |

## Data Sheet 2SB315A-2MBI800VT-170E

| Electrical insulation              | Test conditions                 | Min | Typ.   | Max  | Units         |
|------------------------------------|---------------------------------|-----|--------|------|---------------|
| Operating voltage                  | Continuous or repeated (Note 4) |     |        | 1200 | $V_{dc}$      |
| Test voltage                       | 50 Hz/1 min (Note 11)           |     |        | 4000 | $V_{AC(eff)}$ |
| Partial discharge extinction volt. | IEC270 (Note 12)                |     | > 1700 |      | $V_{AC(pk)}$  |
| Creep path input-output            |                                 |     | 20     |      | mm            |
| Creep path output-output           |                                 |     | 25     |      | mm            |
| Maximum dV/dt at dV= 1000 V        | Note 13                         | 100 |        |      | kV/ $\mu$ s   |

  

| Collector current           | Remarks | Min | Typ. | Max | Units |
|-----------------------------|---------|-----|------|-----|-------|
| Max. IGBT collector current | Note 14 |     | 1400 |     | A     |

All data refer to +25°C and  $V_{DC} = 15$  V unless otherwise specified

## Footnotes to the key data

- 1) The drivers have a zener diode on each channel for over-voltage protection. When the feed voltage exceeds 16V, this protection may be exposed to thermal overload.
- 2) If the specified power consumption is exceeded, this indicates an overload of the DC/DC converter. It should be noted that these DC/DC converters are not protected against overload.
- 3) Application-specific self-heating of gate drivers and IGBT modules, especially at high switching frequency, must be taken into account. As a rule, the switching frequency is limited due to the switching losses of the IGBT modules. Because CONCEPT cannot predict how the drivers will be incorporated in the user's application, no binding recommended value for self-heating and thus for the maximum useable output power can be made. Users are therefore recommended to check the gate driver's ambient temperature within the system.
- 4) This limit is due to active clamping. Refer to the "Description and Application Manual for 2SB315A SCALE Dual-Channel Plug-and-play IGBT Driver".
- 5) Under-voltage monitoring of the supply voltage to the gate driver. If the voltage drops below this limit, the power modules are switched off.
- 6) The gate current is limited by the gate resistors located on the driver.
- 7) Pulse width of the direct output of the gate drive unit (excluding the delay of the gate resistors).
- 8) The typical blocking time after an error is 1 second. Versions with other blocking times may also be supplied if required.
- 9) Measured from the transition of the turn-on or turn-off command at the host controller to direct output of the gate drive unit (excluding the delay of the gate resistors).
- 10) Refers to the direct output of the gate drive unit (excluding the delay of the gate resistors).
- 11) The test voltage of 4000  $V_{ac(rms)}/50$ Hz may be applied only once during one minute. It should be noted that with this (strictly speaking obsolete) test method, some (minor) damage occurs to the insulation layers due to the partial discharge. Consequently, this test is not performed at CONCEPT as a series test. In the case of repeated insulation tests (e.g. module test, equipment test, system test), the subsequent tests should be performed with a lower test voltage: the test voltage is reduced by 400V for each additional test. The more modern if more elaborate partial-discharge measurement is preferable to such test methods as it is almost entirely non-destructive.
- 12) The partial discharge is not measured for the standard types. Tested and selected types with guaranteed partial-discharge immunity can be supplied for applications with maximum requirements and higher operating voltages (such as railroad applications).
- 13) This specification guarantees that the drive information will be transferred reliably even at a high DC-link voltage and with ultra-fast switching operations.

## Data Sheet 2SB315A-2MBI800VT-170E

- 14) Due to the switching behaviour of the IGBT module and the response time of the IGBT driver the maximum collector current is limited to about 1400A at  $T_j=150^{\circ}\text{C}$  and  $U_{dc}=1200\text{V}$ . At higher currents the desaturation protection of the driver will be activated at turn-on.

### Important Notice

The data contained in this product data sheet is intended exclusively for technically trained staff. Handling all high-voltage equipment involves risk to life. Strict compliance with the respective safety regulations is mandatory!

Any handling of electronic devices is subject to the general specifications for protecting electrostatic-sensitive devices according to international standard IEC 747-1, Chapter IX or European standard EN 100015 (i.e. the workplace, tools, etc. must comply with these standards). Otherwise, this product may be damaged.

### Legal Disclaimer

This data sheet specifies devices but cannot promise to deliver any specific characteristics. No warranty or guarantee is given – either expressly or implicitly – regarding delivery, performance or suitability.

CT-Concept Technologie AG reserves the right to make modifications to its technical data and product specifications at any time without prior notice. The general terms and conditions of delivery of CT-Concept Technologie AG apply.

### Technical Support

CONCEPT provides expert help for your questions and problems:

Internet: [www.IGBT-Driver.com/go/support](http://www.IGBT-Driver.com/go/support)

### Quality

The obligation to high quality is one of the central features laid down in the mission statement of CT-Concept Technologie AG. The quality management system covers all stages of product development and production up to delivery. The drivers of the SCALE series are manufactured to the ISO 9001 standard.

## Data Sheet 2SB315A-2MBI800VT-170E

## Ordering Information

The general terms and conditions of delivery of CT-Concept Technologie AG apply.

Related IGBT

CONCEPT Driver Type #

Fuji 2MBI800VT-170E

2SB315A-2MBI800VT-170E

## Information about Other Products

For drivers adapted to other high-voltage or high-power IGBT modules

Direct link: [www.IGBT-Driver.com/go/plug-and-play](http://www.IGBT-Driver.com/go/plug-and-play)

For other drivers and evaluation systems

Please click: [www.IGBT-Driver.com](http://www.IGBT-Driver.com)

## © Manufacturer

CT-Concept Technologie AG  
A Power Integrations Company  
Johann-Renfer-Strasse 15  
2504 Biel-Bienne  
Switzerland

Phone +41 - 32 - 344 47 47

Fax +41 - 32 - 344 47 40

E-mail [Info@IGBT-Driver.com](mailto:Info@IGBT-Driver.com)

Internet [www.IGBT-Driver.com](http://www.IGBT-Driver.com)

© Copyright 2003...2013 by CT-Concept Technologie AG - Switzerland.

All rights reserved.

We reserve the right to make any technical modifications without prior notice.

Version 1.0 from 2016-05-20