



NEX10[®] CONNECTOR

Miniature Low PIM RF Coax Connector System

- » Space saving miniaturized interconnection
- » Excellent Passive Intermodulation
- » Quick lock & Screw coupling
- » Superior RF performance



NEX10[®] CONNECTOR

Miniature Low PIM RF Coax Connector System

The NEX10[®] is a new small coaxial connector system, offering low PIM and ruggedized design in a compact size, to meet the upcoming space reduction requirements of small cells. As the telecommunications industry moves towards the small cell approach, the radio and antenna become smaller and ask for a small sized, high performing coaxial RF connector.



Product features

- » Small size of 12.7 mm flange height
- » Low PIM, independent of applied torque
- » One interface but two coupling mechanism
 - Screw and Quick lock coupling
- » Robust design for outdoor use
- » High protection of all contact areas
- » Optimized for semiflex and ¼" corrugated cables

Characteristics

- » Impedance: 50Ω
- » Excellent RF performance up to 20 GHz
- » Superior passive intermodulation values
 - better than -166dBc
- » Return loss: ≥ 36dB up to 6 GHz
- » Power rating typ. 100W @ 2 GHz @ 85°C
- » IP 68 watertight solution



APPLICATIONS

- » Small Cell and MIMO
- » Distributed Antenna Systems (DAS) / In-building antennas
- » Antennas, radios and filter output
- » Applications requiring PIM stability in a compact size
- » Multi coax / Blind mate applications



Product portfolio

| | Picture | Part number (P/N) | Cable type | Description | Packaging | Plating |
|--------------|---------|-------------------|-----------------------|--|----------------|------------------|
| Cable types | | 5553.NEX.1410.075 | Flexiform 402 UT 141 | Straight Cable Plug Screw | Bulk packaging | 5 = White bronze |
| | | 5562.NEX.1410.085 | 1/4" corrugated cable | Straight Cable Plug Screw | Bulk packaging | 5 = White bronze |
| | | 5552.NEX.1410.075 | Flexiform 402 UT 141 | Straight Cable Plug Quick lock | Bulk packaging | 5 = White bronze |
| Flange types | | 5550.NEX.2018.195 | - | Straight 4-hole Flange Jack | Tray packaging | 5 = White bronze |
| Adapters | | 5554.NEX.8910.005 | - | Measuring Adapter NEX10(m) - RPC-3.50(f) | Bulk packaging | 5 = White bronze |
| | | 5555.NEX.8910.005 | - | Measuring Adapter NEX10(f) - RPC-3.50(m) | Bulk packaging | 5 = White bronze |



EUROPE

IMS Connector Systems GmbH
Obere Hauptstraße 30
DE-79843 Löffingen

Phone +49 (0) 7654 901-100
Fax +49 (0) 7654 901-199
sales@imscs.com

AMERICAS

IMS Connector Systems Inc.
22305 Golden Canyon Circle
Chatsworth
US-CA 91311

Phone +1 (0) 214 704-1115
salesusa@imscs.com

APAC

IMS Connector Systems Ltd
No 35, Huo Ju Road
SND Science & Technology Park
CN-Suzhou 215011

Phone +86 (0) 512 6808-1816
Fax +86 (0) 512 6825-2388
sales@imscscn.com

IMS CONNECTOR SYSTEMS

HEADQUARTERS, GERMANY
IMS Connector Systems GmbH
Obere Hauptstraße 30
DE-79843 Löffingen

Phone +49 (0) 7654 901-100
Fax +49 (0) 7654 901-199

sales@imscs.com
www.imscs.com



More product information:
www.imscs.com
>> Markets >> Communication