

155-23601



Article Number: 155-23601

Stud Mount Lateral Cable Tie, Stud Diameter .2", 50lbs, 6.0" Long, PA66HS, Black, 500/pkg



Download drawing



Download spec sheet

Base Data

Local Order Number 155-23601

Type T50SOSWSP5E

Color Black (BK)

Features and Benefits

- Special shape provides a .20" lateral adjustment to allow for any misalignment of the stud or incorrect positioning of the tie on the cables.
- Easy to install without the need for a tool.
- Design provides low insertion and high extraction force.

Product Description The low profile stud mount allows for several ties to be installed on top of one another. The features can be used to accommodate applications requiring the fastening of a single bundle or multiple bundles on the same stud.

Fixation Method (FF) Weld Stud Fixing

Identification Plate Position none

Releasable Closure (Yes/No) No

Tie Closure plastic pawl

Variant Outside Serrated

Short Description Stud Mount Lateral Cable Tie, Stud Diameter .2", 50lbs, 6.0" Long, PA66HS, Black, 500/pkg

Product Dimensions

Minimum Tensile Strength (Imperial) 50.0 lbs

Minimum Tensile Strength (Metric) 200 N

Length L (Imperial) 6.0 "

Length L (Metric) 163 mm

Width W (Imperial) 0.18 "

Width W (Metric) 4.6 mm

Height H (Imperial) 0.05 "

Bundle Diameter Min. (Imperial) 0.04 "

Bundle Diameter Min. (Metric) 1.0 mm

Bundle Diameter Max. (Imperial) 1.4 "

Bundle Diameter Max. (Metric) 35.0 mm

Thickness T (Imperial) 0.05 "

Thickness T (Metric) 1.35 mm

Stud Size (Imperial) 0.2 "

Stud Size (Metric) 5.0 mm

Logistics and Packaging

Quantity Per bag
Package Quantity (Metric) 500
Carton Quantity 5000 Pieces
Weight (Metric) 1.6 kg

Material and Specifications

Material Polyamide 6.6 heat stabilized (PA66HS)
Material Shortcut PA66HS
Flammability UL94 V2
Operating Temperature -40°F to +221°F (-40°C to +105°C)
ROHS compliant (Article 4 - 1) Yes