



Contactor, AC-3, 30 kW / 400 V, 2 NO + 2 NC, 110 V AC, 50 Hz, 120 V, 60 Hz, with inserted varistor, 3-pole, Size S2, screw terminal Captive auxiliary switch

|   |  |
|---|--|
| <b>product brand name</b>   | SIRIUS   |
| <b>product designation</b>  | Power contactor                                      |
| <b>product type designation</b>   | 3RT2   |
| <b>General technical data</b>   |  |
| <b>size of contactor</b>  | S2   |
| <b>product extension</b>  |  |
| <ul style="list-style-type: none"> <li>function module for communication</li> <li>auxiliary switch</li> </ul>   | <p>No</p> <p>No</p>                                  |
| <b>power loss [W] for rated value of the current</b>  |  |
| <ul style="list-style-type: none"> <li>at AC in hot operating state</li> <li>at AC in hot operating state per pole</li> <li>without load current share typical</li> </ul>   | <p>11.4 W</p> <p>3.8 W</p> <p>18.5 W</p>             |
| <b>insulation voltage</b>   |  |
| <ul style="list-style-type: none"> <li>of main circuit with degree of pollution 3 rated value</li> <li>of auxiliary circuit with degree of pollution 3 rated value</li> </ul>   | <p>690 V</p> <p>690 V</p>                            |
| <b>surge voltage resistance</b>   |  |
| <ul style="list-style-type: none"> <li>of main circuit rated value</li> <li>of auxiliary circuit rated value</li> </ul>   | <p>6 kV</p> <p>6 kV</p>                              |
| maximum permissible voltage for safe isolation between coil and main contacts according to EN 60947-1   | 400 V  |
| <b>shock resistance at rectangular impulse</b>  |  |
| <ul style="list-style-type: none"> <li>at AC</li> </ul>   | 9.8g / 5 ms, 6.5g / 10 ms                            |
| <b>shock resistance with sine pulse</b>   |  |
| <ul style="list-style-type: none"> <li>at AC</li> </ul>   | 15.3g / 5 ms, 10.1g / 10 ms                          |
| <b>mechanical service life (switching cycles)</b>   |  |
| <ul style="list-style-type: none"> <li>of contactor typical</li> <li>of the contactor with added electronically optimized auxiliary switch block typical</li> <li>of the contactor with added auxiliary switch block typical</li> </ul> | <p>10 000 000</p> <p>5 000 000</p> <p>10 000 000</p> |
| <b>reference code according to IEC 81346-2</b>  | Q  |
| <b>Substance Prohibitance (Date)</b>  | 10/01/2014   |
| <b>Ambient conditions</b>   |  |
| installation altitude at height above sea level maximum   | 2 000 m  |
| <b>ambient temperature</b>  |  |
| <ul style="list-style-type: none"> <li>during operation</li> <li>during storage</li> </ul>  | <p>-25 ... +60 °C</p> <p>-55 ... +80 °C</p>          |
| <b>relative humidity minimum</b>  | 10 %   |
| <b>relative humidity at 55 °C according to IEC 60068-2-30 maximum</b>   | 95 %   |

## Main circuit

|  |                    |
|--|--------------------|
| <b>number of poles for main current circuit</b>                        | 3                  |
| <b>number of NO contacts for main contacts</b>                         | 3                  |
| <b>operating voltage</b>   |                    |
| • at AC-3 rated value maximum  | 690 V              |
| • at AC-3e rated value maximum   | 690 V              |
| <b>operational current</b>   |                    |
| • at AC-1 at 400 V at ambient temperature 40 °C rated value            | 80 A               |
| • at AC-1  |                    |
| — up to 690 V at ambient temperature 40 °C rated value                 | 80 A               |
| — up to 690 V at ambient temperature 60 °C rated value                 | 70 A               |
| • at AC-3  |                    |
| — at 400 V rated value   | 65 A               |
| — at 500 V rated value   | 65 A               |
| — at 690 V rated value   | 47 A               |
| • at AC-3e   |                    |
| — at 400 V rated value   | 65 A               |
| — at 500 V rated value   | 65 A               |
| — at 690 V rated value   | 47 A               |
| • at AC-4 at 400 V rated value   | 55 A               |
| • at AC-5a up to 690 V rated value                                     | 70.4 A             |
| • at AC-5b up to 400 V rated value                                     | 53.9 A             |
| • at AC-6a   |                    |
| — up to 230 V for current peak value n=20 rated value                  | 56.9 A             |
| — up to 400 V for current peak value n=20 rated value                  | 56.9 A             |
| — up to 500 V for current peak value n=20 rated value                  | 56.9 A             |
| — up to 690 V for current peak value n=20 rated value                  | 47 A               |
| • at AC-6a   |                    |
| — up to 230 V for current peak value n=30 rated value                  | 38 A               |
| — up to 400 V for current peak value n=30 rated value                  | 38 A               |
| — up to 500 V for current peak value n=30 rated value                  | 38 A               |
| — up to 690 V for current peak value n=30 rated value                  | 38 A               |
| minimum cross-section in main circuit at maximum AC-1 rated value      | 25 mm <sup>2</sup> |
| <b>operational current for approx. 200000 operating cycles at AC-4</b> |                    |
| • at 400 V rated value   | 28 A               |
| • at 690 V rated value   | 22 A               |
| <b>operational current</b>   |                    |
| • <b>at 1 current path at DC-1</b>                                     |                    |
| — at 24 V rated value  | 55 A               |
| — at 110 V rated value   | 4.5 A              |
| — at 220 V rated value   | 1 A                |
| — at 440 V rated value   | 0.4 A              |
| — at 600 V rated value   | 0.25 A             |
| • <b>with 2 current paths in series at DC-1</b>                        |                    |
| — at 24 V rated value  | 55 A               |
| — at 110 V rated value   | 45 A               |
| — at 220 V rated value   | 5 A                |
| — at 440 V rated value   | 1 A                |
| — at 600 V rated value   | 0.8 A              |
| • <b>with 3 current paths in series at DC-1</b>                        |                    |

|  |   |
|--|---|
| <ul style="list-style-type: none"> <li>— at 24 V rated value</li> <li>— at 110 V rated value</li> <li>— at 220 V rated value</li> <li>— at 440 V rated value</li> <li>— at 600 V rated value</li> </ul>  | 55 A<br>55 A<br>45 A<br>2.9 A<br>1.4 A  |
| <ul style="list-style-type: none"> <li>● <b>at 1 current path at DC-3 at DC-5</b> <ul style="list-style-type: none"> <li>— at 24 V rated value</li> <li>— at 110 V rated value</li> <li>— at 220 V rated value</li> <li>— at 440 V rated value</li> <li>— at 600 V rated value</li> </ul> </li> </ul>  | 35 A<br>2.5 A<br>1 A<br>0.1 A<br>0.06 A   |
| <ul style="list-style-type: none"> <li>● <b>with 2 current paths in series at DC-3 at DC-5</b> <ul style="list-style-type: none"> <li>— at 24 V rated value</li> <li>— at 110 V rated value</li> <li>— at 220 V rated value</li> <li>— at 440 V rated value</li> <li>— at 600 V rated value</li> </ul> </li> </ul>   | 55 A<br>25 A<br>5 A<br>0.27 A<br>0.16 A   |
| <ul style="list-style-type: none"> <li>● <b>with 3 current paths in series at DC-3 at DC-5</b> <ul style="list-style-type: none"> <li>— at 24 V rated value</li> <li>— at 110 V rated value</li> <li>— at 220 V rated value</li> <li>— at 440 V rated value</li> <li>— at 600 V rated value</li> </ul> </li> </ul>   | 55 A<br>55 A<br>25 A<br>0.6 A<br>0.35 A   |
| <b>operating power</b> <ul style="list-style-type: none"> <li>● at AC-2 at 400 V rated value</li> <li>● at AC-3               <ul style="list-style-type: none"> <li>— at 230 V rated value</li> <li>— at 400 V rated value</li> <li>— at 500 V rated value</li> <li>— at 690 V rated value</li> </ul> </li> <li>● at AC-3e               <ul style="list-style-type: none"> <li>— at 230 V rated value</li> <li>— at 400 V rated value</li> <li>— at 500 V rated value</li> <li>— at 690 V rated value</li> </ul> </li> </ul> | 30 kW<br><br>18.5 kW<br>30 kW<br>37 kW<br>37 kW<br><br>18.5 kW<br>30 kW<br>37 kW<br>37 kW   |
| <b>operating power for approx. 200000 operating cycles at AC-4</b> <ul style="list-style-type: none"> <li>● at 400 V rated value</li> <li>● at 690 V rated value</li> </ul>  | 14.7 kW<br>20 kW  |
| <b>operating apparent power at AC-6a</b> <ul style="list-style-type: none"> <li>● up to 230 V for current peak value n=20 rated value</li> <li>● up to 400 V for current peak value n=20 rated value</li> <li>● up to 500 V for current peak value n=20 rated value</li> <li>● up to 690 V for current peak value n=20 rated value</li> </ul>  | 22.6 kVA<br>39.4 kVA<br>49.2 kVA<br>56.1 kVA  |
| <b>operating apparent power at AC-6a</b> <ul style="list-style-type: none"> <li>● up to 230 V for current peak value n=30 rated value</li> <li>● up to 400 V for current peak value n=30 rated value</li> <li>● up to 500 V for current peak value n=30 rated value</li> <li>● up to 690 V for current peak value n=30 rated value</li> </ul>  | 15.1 kVA<br>26.2 kVA<br>32.8 kVA<br>45.3 kVA  |
| <b>short-time withstand current in cold operating state up to 40 °C</b> <ul style="list-style-type: none"> <li>● limited to 1 s switching at zero current maximum</li> <li>● limited to 5 s switching at zero current maximum</li> <li>● limited to 10 s switching at zero current maximum</li> <li>● limited to 30 s switching at zero current maximum</li> <li>● limited to 60 s switching at zero current maximum</li> </ul>  | 1 055 A; Use minimum cross-section acc. to AC-1 rated value<br>730 A; Use minimum cross-section acc. to AC-1 rated value<br>520 A; Use minimum cross-section acc. to AC-1 rated value<br>336 A; Use minimum cross-section acc. to AC-1 rated value<br>272 A; Use minimum cross-section acc. to AC-1 rated value |
| <b>no-load switching frequency</b> <ul style="list-style-type: none"> <li>● at AC</li> </ul>   | 5 000 1/h   |
| <b>operating frequency</b> <ul style="list-style-type: none"> <li>● at AC-1 maximum</li> <li>● at AC-2 maximum</li> </ul>  | 800 1/h<br>400 1/h  |

|   |   |
|---|---|
| <ul style="list-style-type: none"> <li>• at AC-3 maximum</li> </ul>                   | 700 1/h   |
| <ul style="list-style-type: none"> <li>• at AC-3e maximum</li> </ul>                  | 700 1/h   |
| <ul style="list-style-type: none"> <li>• at AC-4 maximum</li> </ul>                   | 200 1/h   |
| <b>Control circuit/ Control</b>   |   |
| <b>type of voltage of the control supply voltage</b>                                  | AC  |
| <b>control supply voltage at AC</b>   |   |
| <ul style="list-style-type: none"> <li>• at 50 Hz rated value</li> </ul>              | 230 V   |
| <ul style="list-style-type: none"> <li>• at 60 Hz rated value</li> </ul>              | 230 V   |
| <b>operating range factor control supply voltage rated value of magnet coil at AC</b> |   |
| <ul style="list-style-type: none"> <li>• at 50 Hz</li> </ul>                          | 0.8 ... 1.1                                     |
| <ul style="list-style-type: none"> <li>• at 60 Hz</li> </ul>                          | 0.8 ... 1.1                                     |
| <b>design of the surge suppressor</b>   | with varistor                                   |
| <b>apparent pick-up power of magnet coil at AC</b>                                    |   |
| <ul style="list-style-type: none"> <li>• at 50 Hz</li> </ul>                          | 212 VA  |
| <ul style="list-style-type: none"> <li>• at 60 Hz</li> </ul>                          | 188 VA  |
| <b>inductive power factor with closing power of the coil</b>                          |   |
| <ul style="list-style-type: none"> <li>• at 50 Hz</li> </ul>                          | 0.69  |
| <ul style="list-style-type: none"> <li>• at 60 Hz</li> </ul>                          | 0.65  |
| <b>apparent holding power of magnet coil at AC</b>                                    |   |
| <ul style="list-style-type: none"> <li>• at 50 Hz</li> </ul>                          | 18.5 VA   |
| <ul style="list-style-type: none"> <li>• at 60 Hz</li> </ul>                          | 16.5 VA   |
| <b>inductive power factor with the holding power of the coil</b>                      |   |
| <ul style="list-style-type: none"> <li>• at 50 Hz</li> </ul>                          | 0.36  |
| <ul style="list-style-type: none"> <li>• at 60 Hz</li> </ul>                          | 0.39  |
| <b>closing delay</b>  |   |
| <ul style="list-style-type: none"> <li>• at AC</li> </ul>                             | 10 ... 80 ms                                    |
| <b>opening delay</b>  |   |
| <ul style="list-style-type: none"> <li>• at AC</li> </ul>                             | 10 ... 18 ms                                    |
| <b>arcing time</b>  | 10 ... 20 ms                                    |
| <b>control version of the switch operating mechanism</b>                              | Standard A1 - A2                                |
| <b>Auxiliary circuit</b>  |   |
| number of NC contacts for auxiliary contacts instantaneous contact                    | 2   |
| number of NO contacts for auxiliary contacts instantaneous contact                    | 2   |
| operational current at AC-12 maximum  | 10 A  |
| <b>operational current at AC-15</b>   |   |
| <ul style="list-style-type: none"> <li>• at 230 V rated value</li> </ul>              | 6 A   |
| <ul style="list-style-type: none"> <li>• at 400 V rated value</li> </ul>              | 3 A   |
| <ul style="list-style-type: none"> <li>• at 500 V rated value</li> </ul>              | 2 A   |
| <ul style="list-style-type: none"> <li>• at 690 V rated value</li> </ul>              | 1 A   |
| <b>operational current at DC-12</b>   |   |
| <ul style="list-style-type: none"> <li>• at 24 V rated value</li> </ul>               | 10 A  |
| <ul style="list-style-type: none"> <li>• at 48 V rated value</li> </ul>               | 6 A   |
| <ul style="list-style-type: none"> <li>• at 60 V rated value</li> </ul>               | 6 A   |
| <ul style="list-style-type: none"> <li>• at 110 V rated value</li> </ul>              | 3 A   |
| <ul style="list-style-type: none"> <li>• at 125 V rated value</li> </ul>              | 2 A   |
| <ul style="list-style-type: none"> <li>• at 220 V rated value</li> </ul>              | 1 A   |
| <ul style="list-style-type: none"> <li>• at 600 V rated value</li> </ul>              | 0.15 A  |
| <b>operational current at DC-13</b>   |   |
| <ul style="list-style-type: none"> <li>• at 24 V rated value</li> </ul>               | 6 A   |
| <ul style="list-style-type: none"> <li>• at 48 V rated value</li> </ul>               | 2 A   |
| <ul style="list-style-type: none"> <li>• at 60 V rated value</li> </ul>               | 2 A   |
| <ul style="list-style-type: none"> <li>• at 110 V rated value</li> </ul>              | 1 A   |
| <ul style="list-style-type: none"> <li>• at 125 V rated value</li> </ul>              | 0.9 A   |
| <ul style="list-style-type: none"> <li>• at 220 V rated value</li> </ul>              | 0.3 A   |
| <ul style="list-style-type: none"> <li>• at 600 V rated value</li> </ul>              | 0.1 A   |
| <b>contact reliability of auxiliary contacts</b>                                      | 1 faulty switching per 100 million (17 V, 1 mA) |
| <b>UL/CSA ratings</b>   |   |

|   |  |
|---|--|
| <b>full-load current (FLA) for 3-phase AC motor</b>   |  |
| <ul style="list-style-type: none"> <li>• at 480 V rated value</li> <li>• at 600 V rated value</li> </ul>  | <p>65 A<br/>52 A</p>   |
| <b>yielded mechanical performance [hp]</b>  |  |
| <ul style="list-style-type: none"> <li>• for single-phase AC motor <ul style="list-style-type: none"> <li>— at 110/120 V rated value</li> <li>— at 230 V rated value</li> </ul> </li> <li>• for 3-phase AC motor <ul style="list-style-type: none"> <li>— at 200/208 V rated value</li> <li>— at 220/230 V rated value</li> <li>— at 460/480 V rated value</li> <li>— at 575/600 V rated value</li> </ul> </li> </ul>   | <p>5 hp<br/>10 hp<br/>20 hp<br/>20 hp<br/>50 hp<br/>50 hp</p>  |
| <b>contact rating of auxiliary contacts according to UL</b>   | A600 / Q600  |
| <b>Short-circuit protection</b>   |  |
| <b>design of the fuse link</b>  |  |
| <ul style="list-style-type: none"> <li>• for short-circuit protection of the main circuit <ul style="list-style-type: none"> <li>— with type of coordination 1 required</li> <li>— with type of assignment 2 required</li> </ul> </li> <li>• for short-circuit protection of the auxiliary switch required</li> </ul>   | <p>gG: 250 A (690 V, 100 kA), aM: 160 A (690 V, 100 kA), BS88: 200 A (415 V, 80 kA)<br/>gG: 125A (690V,100kA), aM: 63A (690V,100kA), BS88: 100A (415V,80kA)<br/>gG: 10 A (500 V, 1 kA)</p> |
| <b>Installation/ mounting/ dimensions</b>   |  |
| <b>mounting position</b>  | +/-180° rotation possible on vertical mounting surface; can be tilted forward and backward by +/- 22.5° on vertical mounting surface   |
| <b>fastening method</b>   | screw and snap-on mounting onto 35 mm standard mounting rail according to DIN EN 60715   |
| <ul style="list-style-type: none"> <li>• side-by-side mounting</li> </ul>   | Yes  |
| <b>height</b>   | 114 mm   |
| <b>width</b>  | 55 mm  |
| <b>depth</b>  | 174 mm   |
| <b>required spacing</b>   |  |
| <ul style="list-style-type: none"> <li>• with side-by-side mounting <ul style="list-style-type: none"> <li>— forwards</li> <li>— upwards</li> <li>— downwards</li> <li>— at the side</li> </ul> </li> <li>• for grounded parts <ul style="list-style-type: none"> <li>— forwards</li> <li>— upwards</li> <li>— at the side</li> <li>— downwards</li> </ul> </li> <li>• for live parts <ul style="list-style-type: none"> <li>— forwards</li> <li>— upwards</li> <li>— downwards</li> <li>— at the side</li> </ul> </li> </ul> | <p>10 mm<br/>10 mm<br/>10 mm<br/>0 mm<br/>10 mm<br/>10 mm<br/>6 mm<br/>10 mm<br/>10 mm<br/>10 mm<br/>6 mm</p>  |
| <b>Connections/ Terminals</b>   |  |
| <b>type of electrical connection</b>  |  |
| <ul style="list-style-type: none"> <li>• for main current circuit</li> <li>• for auxiliary and control circuit</li> <li>• at contactor for auxiliary contacts</li> <li>• of magnet coil</li> </ul>  | <p>screw-type terminals<br/>screw-type terminals<br/>Screw-type terminals<br/>Screw-type terminals</p>   |
| <b>type of connectable conductor cross-sections</b>   |  |
| <ul style="list-style-type: none"> <li>• for main contacts <ul style="list-style-type: none"> <li>— solid or stranded</li> <li>— finely stranded with core end processing</li> </ul> </li> <li>• at AWG cables for main contacts</li> </ul>   | <p>2x (1 ... 35 mm<sup>2</sup>), 1x (1 ... 50 mm<sup>2</sup>)<br/>2x (1 ... 25 mm<sup>2</sup>), 1x (1 ... 35 mm<sup>2</sup>)<br/>2x (18 ... 2), 1x (18 ... 1)</p>                          |
| <b>connectable conductor cross-section for main contacts</b>  |  |
| <ul style="list-style-type: none"> <li>• finely stranded with core end processing</li> </ul>  | 1 ... 35 mm <sup>2</sup>   |

|  |  |
|--|--|
| <b>connectable conductor cross-section for auxiliary contacts</b><br><ul style="list-style-type: none"> <li>• solid or stranded</li> <li>• finely stranded with core end processing</li> </ul>   | 0.5 ... 2.5 mm <sup>2</sup><br>0.5 ... 2.5 mm <sup>2</sup>   |
| <b>type of connectable conductor cross-sections</b><br><ul style="list-style-type: none"> <li>• for auxiliary contacts <ul style="list-style-type: none"> <li>— solid or stranded</li> <li>— finely stranded with core end processing</li> </ul> </li> <li>• at AWG cables for auxiliary contacts</li> </ul> | 2x (0.5 ... 1.5 mm <sup>2</sup> ), 2x (0.75 ... 2.5 mm <sup>2</sup> )<br>2x (0.5 ... 1.5 mm <sup>2</sup> ), 2x (0.75 ... 2.5 mm <sup>2</sup> )<br>2x (20 ... 16), 2x (18 ... 14) |
| <b>AWG number as coded connectable conductor cross section</b><br><ul style="list-style-type: none"> <li>• for main contacts</li> <li>• for auxiliary contacts</li> </ul>  | 18 ... 1<br>20 ... 14  |

**Safety related data**

|  |  |
|--|--|
| <b>product function</b><br><ul style="list-style-type: none"> <li>• mirror contact according to IEC 60947-4-1</li> <li>• positively driven operation according to IEC 60947-5-1</li> </ul>       | Yes<br>No  |
| B10 value with high demand rate according to SN 31920  | 1 000 000  |
| <b>proportion of dangerous failures</b><br><ul style="list-style-type: none"> <li>• with low demand rate according to SN 31920</li> <li>• with high demand rate according to SN 31920</li> </ul> | 40 %<br>73 %                                     |
| failure rate [FIT] with low demand rate according to SN 31920  | 100 FIT  |
| T1 value for proof test interval or service life according to IEC 61508  | 20 y   |
| <b>protection class IP on the front according to IEC 60529</b>   | IP20   |
| <b>touch protection on the front according to IEC 60529</b>  | finger-safe, for vertical contact from the front |
| <b>suitability for use</b><br><ul style="list-style-type: none"> <li>• safety-related switching on</li> <li>• safety-related switching OFF</li> </ul>  | Yes<br>Yes                                       |

**Certificates/ approvals**

**General Product Approval**



[Confirmation](#)



[KC](#)



|            |  |                                  |                          |
|------------|--|----------------------------------|--------------------------|
| <b>EMC</b> | <b>Functional Safety/Safety of Machinery</b> | <b>Declaration of Conformity</b> | <b>Test Certificates</b> |
|------------|--|----------------------------------|--------------------------|



[Type Examination Certificate](#)



[Type Test Certificates/Test Report](#)

[Special Test Certificate](#)

**Marine / Shipping**



|                          |              |                |                       |
|--------------------------|--------------|----------------|-----------------------|
| <b>Marine / Shipping</b> | <b>other</b> | <b>Railway</b> | <b>Dangerous Good</b> |
|--------------------------|--------------|----------------|-----------------------|



**Further information**

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RT2037-1CK64-3MA0>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RT2037-1CK64-3MA0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RT2037-1CK64-3MA0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)


[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RT2037-1CK64-3MA0&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RT2037-1CK64-3MA0&lang=en)

Characteristic: Tripping characteristics, I<sup>2</sup>t, Let-through current

<https://support.industry.siemens.com/cs/ww/en/ps/3RT2037-1CK64-3MA0/char>

Further characteristics (e.g. electrical endurance, switching frequency)

<http://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3RT2037-1CK64-3MA0&objecttype=14&gridview=view1>



last modified:

2/15/2022