



CIRCUIT 6 POSITION

- NOTES:
1. ALL DIMENSIONS IN MM
 2. GENERAL TOLERANCE: X.X=±0.4
X.XX=±0.25
 3. TERM. NOS. FOR REFERENCE ONLY.
 4. CONTACT RATINGS: 25mA @24VDC. (Switch)
100mA @50VDC. (Carry)
 5. CONTACT MATERIAL:
CONTACTS: (MOVABLE) Copper w/Gold Plate
TERMINALS: BRASS w/Gold Plate
 6. INSULATION RESISTANCE:
100 Mega-OHMS min. @500VDC
 7. CONTACT RESISTANCE:
50 MILLI-OHMS typical @2-4VDC @100mA
 8. OPERATING TEMP.:
-40°C to +80°C
 9. PACKAGE: TAPE AND REEL
 10. 2002/95/EC (ROHS) COMPLIANT

RECOMMENDED P.C.B. LAYOUT



KAJ06L GGR

REV.	ECN No.	DESCRIPTION	DATE	CHKD
A	16637	RELEASED FOR PRODUCTION	11/10/06	TN

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED

SCALE	DATE	DR	DWG	REV
2:1	11/10/2006	TN	W825133	A