

## 952926CFLF

**Category:** Desktop Chipsets

**Generic Part:** 952926

**Market Group:** PC CLOCK

**Description:** ICS

ICS952926 is a 48 pin clock chip for VIA VX/CX 700 style chipsets. When used with a fanout DDR buffer, such as the 93788, it provides all the necessary clock signals for such a system.

**Output Features:** 3 - 0.7V current-mode differential CPU pairs

- 10 - PCI, 3 free running, 33MHz
- 2 - REF, 14.318MHz
- 3 - 3V66, 66.66MHz
- 1 - 48MHz
- 1 - 24/48MHz
- 2 - 25MHz, 2 free running @2.5V or 3.3V



### Parameters

Temperature	C
Voltage	3.3 V
Package	SSOP 48
Speed	NA
Status	Active
Sample	Yes
Minimum Order Quantity	120
Factory Order Increment	30

### Distributor Inventory

No Pricing information is available from our Distributors at this time.

### Documents

Type	Title	Size	Revision Date
Misc	PC Clocks Contact Info	61 KB	05/29/2007

### Package

Package	SSOP 48 (PVG48)
Description	SSOP 300 ML
Status	Active
Class	PLASTIC
Category	Green
Pb (Lead) Free	Yes
Mark	F
Package Type	SSOP
Lead Count	48
Length	15.9 mm
Width	7.5 mm
Thickness	2.3 mm
Pitch	0.64 mm
Tube / Tray	TUBE
Quantity per Tube/Tray	30
Quantity per Reel	1000
Moisture Sensitivity Level (MSL)	1
Moisture Exposure Floor Life	Unlimited@<30C/85% RH
Peak Reflow Temperature	260Å°C
Rebake Conditions	NA
Related Package Documents	<a href="#">view documents</a>