



NOTES: Finish (Plating Thickness in Micro-inches)

1. Brass
2. Thin Gold over Nickel Pl. 50 Min. Thick over Copper Pl. 50 Min. Thick
3. Gold Pl. 3 Min Thick over Nickel Pl. 50 Min. Thick over Copper Pl. 50 Min. Thick
4. Teflon
5. Passivated

Dimensions are in Inches			
Unless Otherwise Specified Tolerances			
0.5-6	=	±0.2	
6-30	=	±0.4	
30-120	=	±0.6	
120-315	=	±1	
315-1000	=	±1.6	
1000-2000	=	±2.4	

Part No.		Title <b>SMA Crimp Plug</b> (For RG-58, 58A, 58C, 141, LMR195)
Approved	Date 8-30-2013	
Checked	Date 8-30-2013	
Drawn	Date 8-30-2013	

<b>NTE Electronics</b>	
Title <b>SMA Crimp Plug</b> (For RG-58, 58A, 58C, 141, LMR195)	
Drawing No. <b>06-S003</b>	
File No.	

No	Description	Material	Finish	Q'ty	Drawing No.	Scale	4/1	Issue	A2
8	Ferrule	Copper	Note 2	1					
7	Insulator	Note 4	Natural	1					
6	Contact Pin	Note 1	Note 3	1					
5	Gasket	Silicone	Red	1					
4	Retainer Ring	SUS 304	Note 5	1					
3	Insulator	Note 4	Natural	1					
2	Body	Note 1	Note 2	1					
1	Shell	Note 1	Note 2	1					

A

A