



wire connector large 3 units accessory for: 3VA5 250

Model	
product brand name	SETRON
product designation	accessories
Product version	circular conductor terminal
Accessories	Wire connector

General technical data	
designation / of the terminal	TA2.2

Connections according IEC	
connectable conductor cross-section	
<ul style="list-style-type: none"> for copper cable / stranded / minimum for copper cable / stranded / maximum for aluminum cable / stranded / minimum for aluminum cable / stranded / maximum 	50 mm ² 240 mm ² 50 mm ² 240 mm ²
stripped length	30,5 mm
tightening torque / when using copper cables	
<ul style="list-style-type: none"> stranded finely stranded 	50 - 150 mm ² : 31.1 Nm 50 - 150 mm ² : 31.1 Nm

Connections according UL	
permissible temperature / of connectable conductor / according to UL 486A-486B	75 °C
stripped length	1.2 in
connectable conductor cross-section	
<ul style="list-style-type: none"> for copper cable / stranded / minimum for copper cable / stranded / maximum for copper cable / finely stranded / minimum for copper cable / finely stranded / maximum for aluminum cable / stranded / minimum for aluminum cable / stranded / maximum 	2 AWG 350 kcmil 2 AWG 350 kcmil 2 AWG 350 kcmil
tightening torque / when using copper cables	
<ul style="list-style-type: none"> stranded finely stranded 	2 AWG - 350 kcmil: 275 lb-in 2 AWG - 350 kcmil: 275 lb-in

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VA9233-0JJ13>





Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3VA9233-0JJ13>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VA9233-0JJ13

CAX-Online-Generator



last modified:

7/5/2022 

