

# ATP19 Series Anti-Vandal Sealed Pushbutton Switch

## Features/Benefits

- Momentary or Lock version
- IP67 sealed & IK10 (Stainless steel bushing)
- Capable of up to 3A resistive load
- 50,000 life cycle at full load
- Various colors of LED illuminate indicator
- Choices of pushbutton with symbol on spot, ring or power logo

## Typical Applications

- Control Panels including car park and traffic light
- Industrial Instruments
- Lifts / Escalator
- Communication equipment
- Alarm, safety and security systems



C&K US

## Specifications

FUNCTION: Single pole and double poles  
CONTACT ARRANGEMENT: N.O. and N.C.  
MOUNTING TYPE: Threaded front panel mount  
TORQUE FOR THREADED BODY: 5-14 Nm

## Mechanical

OPERATING LIFE: Momentary 1,000,000 cycles  
Self-lock 500,000 cycles  
TOTAL TRAVEL: about 3.2 mm  
OPERATING FORCE: 1 pole 2.5 ± 1N  
2 pole 3.5 ± 1N

## Electrical

CONTACT RATING: 1th 5A/250VAC  
3A / 250VAC  
3A / 28VDC  
OPERATING LIFE: 50,000 make-and-break cycles at full load  
DIELECTRIC STRENGTH: 2,000 V RMS @ sea level  
INSULATION RESISTANCE: 1,000 MΩ min. @ 500 VDC  
INITIAL CONTACT RESISTANCE : 50 mΩ max @1A 12VDC

## Materials

BUSHING: Stainless steel / Nickel plated brass / Aluminum alloy  
BASE: PBT (UL 94-A0), PC (UL 94-V2)  
ACTUATOR: PC (UL 94-V2); Stainless steel / Nickel plated brass / Aluminum alloy  
INTERNAL ASSEMBLY: POM / PA66  
SPRING: Steel  
SEALING / O-ring: Silicone  
TERMINALS: Brass with silver or gold plated  
CONTACT: Copper, silver plated

## Operating Environment

OPERATING TEMPERATURE: -20°C to +55°C  
SEALING / PROTECTION: IP67 / IK10 (Stainless steel bushing)

**NOTE:** Specifications and materials listed above are for switches with standard options.  
For information on specific and custom switches, please contact Customer Service.

## Build-A-Switch

To order, simply select desired option from each category and place in the appropriate box.



**Designation** \_\_\_\_\_  
**ATP19 Series**

**Actuator Style** \_\_\_\_\_  
**S** Standard  
**R** Raised #  
**D** Dome without LED only ###

**Actuator Indicator** \_\_\_\_\_  
**L0** Without LED \*  
**L1** Fix ring \*  
**L2** Spot \*  
**L3** Moving ring \* (standard actuator only)  
**L4** Power logo \*\*  
**L5** Moving ring & Power logo \*\* (standard actuator only)

**LED Illumination** \_\_\_\_\_

**Terminal plating** \_\_\_\_\_  
**Q** Silver  
**G** Gold

**Termination** \_\_\_\_\_  
**03** STD solder lug  
**04** Short solder lug  
**W1** Wire lead 500mm \*\*\*  
**W2** Wire lead 1,000mm \*\*\*

**Mechanical function** \_\_\_\_\_  
**A** Momentary  
**E** Lock

**Contact arrangement** \_\_\_\_\_  
**S** SPDT  
**D** DPDT


Color	Dual color
<b>0</b> Without LED	<b>A</b> Red & Green
<b>2</b> White	<b>B</b> Red & Blue
<b>3</b> Red	<b>D</b> Blue & Yellow
<b>5</b> Yellow	<b>G</b> Red & Yellow
<b>6</b> Green	<b>H</b> Green & Yellow
<b>7</b> Blue	<b>J</b> Orange & Green

**LED voltage (20mA)**

<b>00</b>	Without LED
<b>03</b>	3V
<b>06</b>	6V
<b>12</b>	12V
<b>24</b>	24V
<b>36</b>	36V
<b>A1</b>	110V AC
<b>A2</b>	220V AC

Round	Double D shape
<b>B0</b> Stainless (Natural)	<b>M0</b> Stainless (Natural)
<b>B3</b> Al alloy (Black anodized) ##	<b>M3</b> Al alloy (Black anodized) ##

- \* Available on round bushing only
- \*\* Available on double D-shape bushing only
- \*\*\* Available upon request, please contact your sales representative for details
- # Come in B0 & M0 with L1 or L4 indicator only
- ## Come in S style actuator only & no L5 indicator
- ### Without LED & for B0 & M0 bushing type only



Dimensions are shown: mm (inches)  
Specifications and dimensions subject to change



17 Mar 23




# ATP19 Series Anti-Vandal Sealed Pushbutton Switch


Pushbutton  
A

## STANDARD VIEW

**ROUND BUSHING**




**DOUBLE-D BUSHING**




## ACTUATOR STYLE


**S STANDARD**



**R RAISED**




**D DOME**




## ACTUATOR INDICATOR


**L0 WITHOUT LED**




**L1 FIX RING**




**L3 MOVING RING**




**L2 SPOT**



**L4 POWER LOGO**



**L5 POWER & MOVING RING**




# ATP19 Series Anti-Vandal Sealed Pushbutton Switch




A  
Pushbutton

## CIRCUIT


SPDT




SPDT - SINGLE COLOR LED




SPDT - DUAL COLOR LED




DPDT



DPDT - SINGLE COLOR LED




DPDT - DUAL COLOR LED




## TERMINATION



**03** SOLDERLUG



**04** SHORT SOLDER LUG





**W1 OR W2** WIRE LEAD



## HARDWARE

**HEX NUT**

Order PN: ATP19-HN



**O RING**

Order PN: ATP19-OR

