



PC board drilling dimensions
(after plating – thickness: 1.60 to 3.20 mm)

LEAD FREE PART NUMBER

PART NUMBER	
flash gold	D50P91C4P*00LF
0.76µ gold	D50P91C6P*00LF

Threaded ØT M3 = L
Threaded ØT 4.40 = X

GENERAL CHARACTERISTICS AND ROHS INFORMATIONS:
SEE DRAWING C01-8646-0001

Notes:

1) The nut can protrude above the surface of insulator but maintaining the footprint dimension 6.0±0.15 mm.

mat'l. code		surface		tolerance		projection		product family	
-		ISO 1302 ✓		ISO 406 ISO 1101				D-SUB	
ltr	ecn no	dr	date	tolerances unless otherwise specified				title	
E	ELX-I-22878	AB	2015/01/06	.0±0.1		MM		MALE CONNECTOR DELTA-D STRAIGHT – PRESS FIT	
				angles	linear	scale 2:1		dwg no	
				0°±2'	.00±0.1			sheet 1 of 1	
				dr	PESSON	1996/07/24		size	
				enr	ALIAS BABU	2015/01/06		A3	
				chr	MITHUN PAUL	2015/01/06		C01-8646-0463	
				app	BIJU K PAUL	2015/01/06		type	
								Product Customer Drawing	
sheet index	revision sheet	E	1						

