

APPLICATOR PARTS LIST

TYPE

LENGTHWISE

AMPLIVAR
SPLICE
PIGTAIL

SPECIAL
FLAT ON
CRIMPER
& ANVIL
AMP INCORPORATED
HARRISBURG, PENNA.

NO.	DESCRIPTION	REQ.	PART NO.
1	WIRE CRIMPER	1	455713-4
2	INS. CRIMPER		
3	ANVIL	1	455714-4
4	ANVIL SPACER		
5	SHEAR BLADE	1	693012-1
6	REAR SHEAR PLATE	1	465891-1
7	SHEAR BLADE SPACER		
8	FRONT SHEAR PLATE		
9	REAR ANVIL SPACER PLT.		
10	FRONT ANVIL SPACER PLT.		
11	TOOL SPACER		
12	CRIMP SPACER		
13	FRONT STRIP GUIDE	1	811172-2
14	REAR STRIP GUIDE	1	811173-2
15	RAM	1	471167
16	TOOL HOLDER	1	689633-2
17	CRIMP & BLADE MT	1	465755-2
18	SCREW, SOC. HD. 10-32 x 5/8	1	3-21000-6
19	APPLICATOR MOUNT ASSY.	1	471707-4
20	BASE PLATE		
21	BASE BLOCK		
22	STRIP GUIDE PLATE		
23	ANVIL HOLDER		
24	AUX. ANVIL HOLDER		
25	STRIPPER	1	389072-3
26	STRIPPER MOUNT		
27	RETAINER PLATE		
28	STRIPPER MOUNT BRACKET		
29	STRIPPER BUSHING		
30	STOCK DRAG	1	376666
31	STOCK DRAG HANDLE		
32	STOCK DRAG STUD - REAR	1	354045-1
33	STOCK DRAG SPRING - REAR	1	1-23847-1
34	STOCK DRAG ADJ. SCREW	2	372997
35	FEED FINGER HOLDER		
36	FEED FINGER	1	452817-1
37	FEED FINGER TIP		
38	FEED FINGER SPACER		
39	BASE CASTING	1	570238
40	GUARD	1	460182-1
41			

NO.	DESCRIPTION	REQ.	PART NO.
42	SCREW, SOC. HD. CAP	2	811651-5
43	WASHER, LOCK	2	21057-4
44	STRIP HOLD DOWN	1	810640-1
45			
46			
47			
48			
49			
50	DRAG BUSHING - FRONT	1	452836-1
51	DRAG SCREW - FRONT	1	452837-1
52	DRAG SPRING - FRONT	1	370572
53			
54			
55	ELBOW	1	22317-3
56	COPPER TUBE	1	689446-2
57	SCREW, SOC. HD. 1/4-20 x 3/4	1	21001-4
58			
59	LOCK WASHER 1/4 ID	1	21024-6
60	TENSION ADJ. PLATE	1	374999
61			
62			
63			
64			
65	AIR BLAST ASSY.	1	455350-2
MISCELLANEOUS			
66	TOOL SPACER (FOR SETUP) ONLY	-	693619-1
NOTE: PLACE ITEM 66 BETWEEN CRIMP MT. ITEM 17 & ALIGN. GA. DURING SETUP.			
71	LUBRICATOR ASSY.	1	465184-2
72	SYNTHETIC OIL	1	22014-1

125		CRIMPING DATA		TERMINALS
TO APPLY TERMINAL		114-2002		7 SERR. SHIFTRD
WIRE SIZE	CRIMP HEIGHT			62295-
(2) 14 MAG	.088			
CRIMP WIRE	SIZE	TYPE	FEED	
INSULATED	250	F		
CLEARED	BLUNT		.315	
INSULATION RANGE		WIRE RANGE CMA		
		7000-12000		
EXPLODED VIEW		SIM TO		
A-6000		A-6000-5		
REMARKS: 800 FORWARD				
■ DENOTES WEARING PARTS RECOMMEND PURCHASE REPLACEMENT				
THIS APPLICATOR IS TO BE USED ON AMP-O-LECTRIC 1-471273-3				
AMP-O-LECTRIC MECH FEED		ALIGN. GA		DIST. 4
SERIAL NO.		DATE SHIPPED		DESIGNED RAY 7-8-75
				CHK'D 7-9-75
CUSTOMER NAME AND ADDRESS				
APPLICATOR NUMBER				
REV. B2		566210-1		SHEET 1 OF 1

THIS DRAWING IS A CONTROLLED DOCUMENT. © COPYRIGHT 1998 BY AMP INCORPORATED. ALL RIGHTS RESERVED. RELEASED FOR PUBLICATION - MAY, 1998