

# **VE-S6** Binocular Stereoscope with Zoom System

The VE-S6 is the ideal for professional use in higher education, research and industrial procedures. A versatile device, useful in production procedures or quality inspection of industrial products, thanks to its zoom system.

Its Greenough design allows three-dimensional observation of insects and possesses a wide field of observation provided by its eyepieces. The VE-S6 is the perfect device for the dissection and classification of organisms in entomology and taxonomy, as well as livestock for the observation and selection of viable embryos.



### Velab, Co.

USA

VELAB MICROSCOPES is the registered trade mark of Velab, Co.

Velab follows a policy of continuos innovation. Design and specifications are subject to change without prior notice

#### www.velab.net.

# VE-S6 Stereoscopic Binocular Microscope with Zoom System

The VE-S6 is the ideal for professional use in higher education, research and industrial procedures. A versatile device, useful in production procedures or quality inspection of industrial products, thanks to its zoom system.

Its Greenough design allows three-dimensional observation of insects and possesses a wide field of observation provided by its eyepieces. The VE-S6 is the perfect device for the dissection and classification of organisms in entomology and taxonomy, as well as livestock for the observation and selection of viable embryos.

## SPECIFICATIONS

#### EYEPIECES

WF 10X/22 mm with rubber eyecups and diopter adjustment on both eyepieces.

#### HEAD

Binocular head, 45° inclined with zoom adjustment knobs.

#### OBJECTIVE

With zoom system for variable magnifications of 0.67X, 0.7X, 0.8X, 1X, 1.5X, 2X, 3X, 4X and 4.5X (from 6.7 to 45 total increases) and objective cover.

#### STAND

Stative, robust and reinforced with epoxy paint finish.

#### STAGE

Interchangeable between translucent white and double side white/ black, with a pair of stage clips.

#### FOCUSING

Coarse anti-slip control knob with tension adjustment.

#### ILLUMINATION

Transmitted and incident LED light with independent variable intensity control.

**POWER SUPPLY** 110-240V, 50/60 Hz AC adapter.

ACCESSORIES INCLUDED

Dust cover. Operation manual.



