

## FO connectors - VS-V1-C-SCRJ-MNNA-PG9-A1-G - 1419187

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



SCRJ fiber optic connector, IP67, with bayonet locking, metal housing, duplex, with adhesive connection technology, for multi-mode fiber, for cable diameter of 5.0 mm ... 10 mm



EtherNet/IP

### Key commercial data

Packing unit	1 pc
Weight per Piece (excluding packing)	140.0 GRM
Custom tariff number	85366990
Country of origin	Germany

### Technical data

#### Mechanical characteristics

Number of positions	2
Number of slots	1
Locking type	Bayonet locking
Fiber type	Multi-mode 50/125 µm fiberglass
Insertion/withdrawal cycles	500
Connection method	SC duplex
Max. cable diameter	5 mm ... 10 mm
Color	silver

#### Ambient conditions

Ambient temperature (operation)	-40 °C ... 70 °C
Degree of protection	IP67

#### Material data

Inflammability class according to UL 94	V0
Housing material	Zinc die-cast
Material	Metal

# FO connectors - VS-V1-C-SCRJ-MNNA-PG9-A1-G - 1419187

## Technical data

### Electrical characteristics

Number of positions	2
---------------------	---

## Classifications

### eCl@ss

eCl@ss 4.0	27140816
eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27260701
eCl@ss 6.0	27260709
eCl@ss 7.0	27440305
eCl@ss 8.0	27440305

### ETIM

ETIM 2.0	EC001122
ETIM 3.0	EC001122
ETIM 4.0	EC001122
ETIM 5.0	EC001122

### UNSPSC

UNSPSC 6.01	30211832
UNSPSC 7.0901	31261501
UNSPSC 11	31261501
UNSPSC 12.01	31261501
UNSPSC 13.2	39121429

## Approvals

### Approvals

---

Approvals

GOST / GOST

---

Ex Approvals

---

Approvals submitted

# FO connectors - VS-V1-C-SCRJ-MNNA-PG9-A1-G - 1419187

## Approvals

### Approval details

GOST 

GOST 

## Drawings

Dimensioned drawing

