

Connector A 132117 SMA Jack Straight Brass Gold + Heatshrink 50 Ohm RG-174 Continuity/Hi-Pot Connector B SMP-FR-C08-1 SMP Plug Right Angle Beryllium Copper Gold + Heatshrink

Assembly & Label Notes

Assembly label to be placed ~ 2" from end of connector A and/ or heat shrink Assembly shall be built with SN96.5 LEAD FREE solder. See Routing Notes for additional assembly & testing instructions.

[Connector A			Cable			Connector B		
	Part #: Description: Type: Gender: Body Type: Contact Type: Polarity: Impedance: Mounting: Body Material: Body Finish: IP Rating: Contact Material: Contact Finish: Max. Freq.: Booting:	132117	2G316 LMR100 50O	Part #: Description: Dielectric: Shielding: Diameter: Impedance: Sheathing: Testing: Length:	RG-174 RG-174 - PE 0.1 PE Braid 0.1 50 Ohm None Continuity Hi-Pot 1 Meter	Part #: Description: Type: Gender: Body Type: Contact Type: Polarity: Impedance: Mounting: Body Material: Body Finish: IP Rating: Contact Material: Contact Material: Contact Finish: Max. Freq.: Booting: Clocking:	SMP-FR-C08-1 SMP R/A PLUG RG SMP Plug Right Angle Solder Standard 50 Ohm Cable Beryllium Copper Gold None Beryllium Copper Gold 26.5 GHz SMP Plug Right Ang 0°		
Amphenol USTOM CABLE CONTROLLED DOCUMENT - DO NOT COPY THIS DRAWING MAY CONTA PROPRIETARY INFORMATION FOR ANY PURPOSE DETRIME INC. IT MAY NOT BE REPROD IN ANY FORM WITHOUT THE CUSTOM CABLE INC. ACCEPT ESTABLISHES AND AGREEMING			AND MUST NOT BE U TAL TO CUSTOM CAI CED OR TRANSCRIBI VRITTEN CONSENT O ANCE OF THIS DRAWI	ABLE BED DF Part No:			UNLESS SPECIFIED TOLERANCE: 0-18 inches +/. 1/2" over 18" +/- 2% ASSEMBLY: CENTER LABEL IF LENGTH IS LESS THAN 12 INCHES		