



Main

| | |
|---------------------------|---|
| Range | Spacial |
| Extended range | Spacial SF |
| Application | Multi-purpose |
| Product or Component Type | Suitable enclosure |
| Enclosure nominal height | 70.87 in (1800 mm) |
| Enclosure nominal width | 23.62 in (600 mm) |
| Enclosure nominal depth | 19.69 in (500 mm) |
| Enclosure mounting | Floor-standing |
| Device composition | 2 sliding rails 4 mounting plate bracket 1 structure 1 door 1 locking system with handle door 1 rear panel 1 roof |

Complementary

| | |
|-----------------------------|--|
| Structure type | Perforated structure with a pitch of 25 mm Panels and doors built into the structure Vertical uprights joined with top and bottom frames Formed from a single section |
| Door type | Glass front |
| Number of doors | Front 1 |
| Door opening side | Reversible 120 °) |
| Lock type | 4 points lock, handle with 5 mm double bar insert front door |
| Mounting plate description | Without mounting plate |
| Type of gland plate | Without gland plate |
| Accessibility for operation | Front Rear Sides of enclosure |
| Removable parts | Door by screws hinge Rear panel by screws Roof by screws Mounting plate bracket by screws Sliding rail by screws |
| Material | Frame galvanised steel Uprights galvanised steel Door Securit glass Door sheet steel Panels sheet steel Hinge zamak Handle polyamide 6 with 30 % fibre glass |
| Surface finish | Epoxy-polyester powder |
| Color | Enclosure Gray RAL 7035) Handle Black RAL 9005) |
| Net Weight | 196.30 lb(US) (89.040 kg) |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

| | |
|---------------------------|----------------|
| Standards | IEC 62208 |
| NEMA Degree of Protection | NEMA 3R/12 |
| IP degree of protection | IP55 IEC 60529 |
| IK degree of protection | IK08 IEC 62262 |

Ordering and shipping details

| | |
|-----------------------|-------------------------------------|
| Category | 80035-ENCLOSURE SYSTEMS FLOOR MOUNT |
| Discount Schedule | ES1 |
| GTIN | 3606485118598 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 196.30 lb(US) (89.04 kg) |
| Returnability | No |
| Country of origin | ES |

Packing Units

| | |
|------------------------|---------------------|
| Unit Type of Package 1 | PCE |
| Package 1 Height | 75.98 in (193.0 cm) |
| Package 1 width | 25.39 in (64.5 cm) |
| Package 1 Length | 23.23 in (59.0 cm) |

Offer Sustainability

| | |
|----------------------------|--|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|