Product data sheet

Specifications





Limit switch body, Limit switches XC Standard, ZCP, compact, 2NC, slow break

ZCP07

① Discontinued on: 29 June 2023

① Discontinued

Main

wain	
Range of product	Telemecanique Limit switches XC Standard
Series name	Standard compact
Product or component type	Limit switch body
Device short name	ZCP
Design	Compact
Body type	Fixed
Associated head	ZCE28 ZCE63 ZCE11 ZCE27 ZCE14 ZCE06 ZCE12 ZCE05 ZCE10 ZCE01 ZCE05 ZCE10 ZCE01 ZCE07 ZCE02 ZCE65 ZCE64 ZCE65 ZCE64 ZCEH0 ZCE66 ZCE66 ZCE66 ZCE67 ZCE08 ZCE07 ZCE08 ZCE24 ZCE07 ZCE62 ZCE13 ZCEH2
Body material	Plastic
Number of poles	2
Contacts type and composition	2 NC
Contact operation	Slow-break, simultaneous

Complementary

Associated connection component	ZCPEG11 ZCPEF12 ZCPEP16 ZCPEG13 ZCPEP20 ZCPEN12
Electrical connection	Open terminal, clamping capacity: 1 x 0.52 x 2.5 mm²
Contacts insulation form	Zb

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Contacts material	Silver plated contacts
Positive opening	With
Minimum actuation speed	6 m/s
Contact code designation	B300, AC-15 (Ue = 240 V), Ie = 1.5 A conforming to EN/IEC 60947-5-1 appendix A R300, DC-13 (Ue = 250 V), Ie = 0.1 A conforming to EN/IEC 60947-5-1 appendix A
[Ui] rated insulation voltage	300 V conforming to UL 508 500 V (pollution degree 3) conforming to IEC 60947-1 300 V conforming to CSA C22.2 No 14
[Uimp] rated impulse withstand voltage	6 kV conforming to IEC 60664 6 kV conforming to IEC 60947-1
Short-circuit protection	10 A cartridge fuse, type gG
Electrical durability	5000000 cycles, DC-13 120 V, 7 W, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C 5000000 cycles, DC-13 24 V, 13 W, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C 5000000 cycles, DC-13 48 V, 9 W, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C
Width	31 mm
Height	65 mm
Depth	30 mm
Product weight	0.07 kg
Environment	
Product compatibility	XCKP
Ambient air temperature for operation	-2570 °C
Ambient air temperature for storage	-4070 °C
Packing Units	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.5 cm
Package 1 Width	4.1 cm
Package 1 Length	4.1 cm
Package 1 Weight	68.0 g
Offer Sustainability	
Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information gowww.P65Warnings.ca.gov

Contractual warranty

Warranty

18 months

Recommended replacement(s)

ZCP07 is replaced by:

1x



Limit switch body, Limit switches XC Standard, ZCP, compact, 2NC, snap action ZCP29