


Note: parts in bulk,
100SET/bag

ELECTRIC CHARACTERISTICS REQUIREMENTS:

1. Product must be 100% conduction, open circuit short circuit test.
2. Conductive resistance: 20Ω
3. Rated voltage: AC 60V
4. Withstand voltage: AC 200V
5. Insulation resistance: $500m\Omega$
6. Characteristic impedance: 50Ω
7. Adopt environmental protection process and meet ROHS requirements
8. Tensile test: 1.5kg
9. The general tolerance shall prevail if no tolerance is noted

RoHS Compliant

ITEM	PART No.	VENDOR	DESCRIPTION	Q'TY	OVERALL WIRE LENGTH
5	COVER	-	RED HAT PACKING SMA	1	-
4	SMA FEMALE	-	11*1.13-ZYK-BACK PLUG RIVETING AND GOLD PLATING	1	-
3	HEAT SHRINK SLEEVE	-	2.0*18MM BLACK HEAT SHEINK SLEEVE	1	-
2	IPEX-1.13 CONN	-	IPEX-1.13 BRASS GOLD	1	-
1	COAXIAL CABLE	-	RG1.13 DARK GREY-48-TIN-FEP JACKET L=155MM	1	155
MATERIAL SPECIFICATION					

SYM	NAME	DATE	REVISIONS	DRAWN BY	CHECKED BY	APPROVED BY	CONFIRMED BY	DESCRIPTION	CUST. CODE	
③									CUC	
②				LuLu	Iron	Iron	Waleed	RF CABLE	CUC	
①				08/21.20'	08/21.20'	08/21.20'	08/21.20'		CUC	
								SHEET: 1 OF 1	DH50625A	DH-20G50011



DRAWING No. CviLux P/N
DH50625A DH-20G50011