

**Terminal markers
ESO 14/6 DIN A4-BOGEN**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com



The various connector markers from Weidmüller enable users to solve virtually every labelling task on all types of lines. Whether several lines of labelling, ready-to-use markers with standard printing, or individual labelling, whether white or coloured markers or common designations at the clamping points, the comprehensive range of products represent the easy, quick and clear answer to every marking task.

General ordering data

| | |
|------------|---|
| Order No. | 1607740000 |
| Type | ESO 14/6 DIN A4-BOGEN |
| Version | Terminal markers, 34 x 4 mm, Paper, Colour: White |
| GTIN (EAN) | 4008190206130 |
| Qty. | 10 pc(s). |

**Terminal markers
ESO 14/6 DIN A4-BOGEN**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data
Dimensions and weights

| | | | |
|--------|-------|------------|------|
| Length | 34 mm | Width | 4 mm |
| Height | 1 mm | Net weight | 12 g |

Markings

| | | | |
|--|--------|--|-------|
| Can be labelled with thermal transfer printers | No | Can be printed with plotter | Yes |
| Can be written with dot-matrix printer | No | Can be written with laser printer | Yes |
| Colour | White | Conductor O.D. | |
| Material | Paper | Material colour according to resistance code | 9 |
| Number per sheet | 320 | Operating temperature range, max. | 80 °C |
| Operating temperature range, min. | -40 °C | Pin can be written (STI) | Yes |
| Pitch in mm (P) | 6 mm | Speed marking laser | No |

Classifications

| | | | |
|------------|-------------|------------|-------------|
| ETIM 2.0 | EC000761 | ETIM 3.0 | EC000761 |
| UNSPSC | 30-21-18-07 | eClass 4.1 | 24-19-02-19 |
| eClass 5.1 | 27-14-11-37 | eClass 6.2 | 27-14-11-37 |
| eClass 7.1 | 27-14-11-37 | | |

Approvals

| | |
|-----------|---------|
| Approvals | |
| ROHS | Conform |