



NOTES

- 適合ターミナルシリーズ: 503657シリーズ  
APPLICABLE TERMINAL : 503657 SERIES
- 嵌合相手 : 504056シリーズ  
MATE WITH : 504056SERIES
- △ 偶数極に適用  
APPLY FOR EVEN CIRCUIT.
- △ キャビティ番号 : 1桁から2桁の数字にて表示。  
金型番号 : アルファベット1文字にて表示  
CAVITY NO. : 1 TO 2 DIGIT NUMBER  
MOLD NO. : 1 LETTER ON ALPHABET
- 本製品のプラスチック部に黒点等が確認される場合や、色合いが異なる場合がございますが、製品性能に影響はございません。  
THERE IS NO INFLUENCE IN THE PRODUCT PERFORMANCE THOUGH THE BLACK SPOT ETC. MIGHT BE CONFIRMED TO THE PLASTIC PART OF THIS PRODUCT AND THE SHADE MIGHT BE DIFFERENT.
- ELV 及びRoHS適合品  
ELV AND RoHS COMPLIANT

18	23.2	504054-2000	504054-**00	20
B	A	ORDER NO.	CONNECTOR SERIES NO.	CKT

PROPOSED EC NO: J2012-0149 DRWN:TKON CHKD: APPR:NUKITA 2011/07/08 2011/08/10 0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE		SCALE	DESIGN UNITS		THIRD ANGLE PROJECTION	
			MM ONLY		5:1	METRIC			
	10 UNDER	±0.2	DRAWN BY		DATE	TITLE			
	10 OVER 30 UNDER	±0.25	TKON		2011/07/08	2.0 W/B CONN. DUAL REC. CRIMP HSG			
	30 OVER	±0.3	CHECKED BY		DATE				
ANGULAR ±1 °		APPROVED BY		DATE	MOLEX INCORPORATED				
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		NUKITA		2011/08/10	MATERIAL NO.		DOCUMENT NO.		SHEET NO.
		SEE TABLE		SD-504054-001		1 OF 1			
		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION							

PART	MATERIAL
HOUSING	POLYESTER (PBT), UL94V-0 COLOR : NATURAL(WHITE)