Main Range Thalassa **Product name** Thalassa PLA **Enclosure type** Multi-purpose Product or component type Suitable enclosure PLA Version 1000 mm Nominal height Nominal width 1250 mm **Nominal depth Enclosure mounting** Floor-standing **Device composition** 1 top part 2 side part 2 door 2 rear panel

Complementary

| Body type | Sealed top and bottom part assembled with side parts |
|-----------------------------|--|
| Door type | Transparent front |
| Number of doors | 2 door(s) |
| Door opening side | Right and left (120 °) |
| Lock type | 4 points lock, 5 mm double-bar |
| Accessibility for operation | Front Rear |
| Removable parts | Door by hinges Rear panel by fixing element |
| Material | Polyester reinforced with fibreglass |
| Colour | Grey (RAL 7035) |
| Standards | IEC 62208 UL 508 A |
| NEMA degree of protection | NEMA 2 NEMA 1 NEMA 13 NEMA 12 |
| Product certifications | UL/cUL listed DNV Marine |

Veritas

| Electrical insulation class | Class II |
|-------------------------------------|--|
| Environment | |
| IP degree of protection | IP65 conforming to IEC 60529 (completely sealed) |
| IK degree of protection | IK08 conforming to IEC 62262 (glazed door) |
| Fire resistance | 960 °C conforming to IEC 62208 |
| Ambient air temperature for storage | -3590 °C |
| Packing Units | |
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 101.0 cm |
| Package 1 Width | 128.0 cm |
| Package 1 Length | 35.0 cm |
| Package 1 Weight | 47.299 kg |
| Offer Sustainability | |
| Sustainable offer status | Green Premium product |
| REACh Regulation | REACh Declaration |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |
| | |

Recommended replacement(s)