

Shrink sleeve - WMS 12,7 (60X20)RL YE - 0803107

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Shrink sleeve, Roll, yellow, unlabeled, can be labeled with: THERMOMARK W, THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK X1.2, Perforated, Lettering field: 60 x 20 mm



The illustration shows WMS 6,4 (30X10)R

Product Features

- WMS ... shrink sleeves provide permanent and captive conductor and cable marking
- The sleeves are pre-assembled for optimum use of material
- The conductor to be marked is simply threaded through the sleeve and fixed by shrinking the sleeve
- The sleeves remain flexible after shrinking
- Up to four markers per sleeve are separated by perforations
- UL 224 (125°C, 600 V, all tubing)
- CSA.C22.2 No. 198.1 (125°C, 600 V, all tubing)
-

Key commercial data

| | |
|--------------------------------------|----------|
| Packing unit | 1 pc |
| Weight per Piece (excluding packing) | 12.0 GRM |
| Custom tariff number | 39173200 |
| Country of origin | China |

Technical data

Dimensions

| | |
|------------|-------|
| Length (b) | 60 mm |
| Width (a) | 20 mm |

General

| | |
|-----------------------|--------------|
| Color | yellow |
| Base element material | polyolefine |
| Components | Halogen-free |
| Material | Polyolefine |

Shrink sleeve - WMS 12,7 (60X20)RL YE - 0803107

Technical data

General

| | |
|-----------------------------|-----------------------------|
| Wipe resistance | DIN EN 61010-1 (VDE 0411-1) |
| Number of individual labels | 1000 |

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 4.1 | 24190219 |
| eCl@ss 5.1 | 27400401 |
| eCl@ss 6.0 | 27400401 |
| eCl@ss 8.0 | 27400401 |

ETIM

| | |
|----------|----------|
| ETIM 4.0 | EC000217 |
| ETIM 5.0 | EC001530 |