



JKL LAMP NUMBER	VOLTS RATED	AMPS $\pm 10\%$	MSCP $\pm 25\%$	LUMENS $\pm 25\%$	AVERAGE LIFE HRS.	FILAMENT TYPE AND POSITION
1034	12.8	1.80	32.0	402.2	200	C-2R POSITION #2 = 2 FILAMENTS
	14.0	.59	3.0	37.7	5,000	C-2R POSITION #1 = 1 FILAMENT
1157	12.8	2.10	32.0	402.2	1,200	C-2R POSITION #2 = 2 FILAMENTS
	14.0	.59	3.0	37.7	3,000	C-2R POSITION #1 = 1 FILAMENT

		 THIRD ANGLE PROJECTION		DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0.2 2 PL +/- 0.20 ANGLE +/- 0		JKL COMPONENTS CORPORATION			
						TITLE S-8 DOUBLE CONTACT INDEX BAYONET BASE LAMP			
A DIM. CHNG ON CONTACTS TO 6.48/7.08 RELEASED AS CAD		5/18/01	L. WENGSTROM	APPV'D BY	DATE	A SIZE 55335	DRAWING NO. BAYONET DOUBLE CONTACT INDEX S-8		
		5/9/01	- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED		SCALE	RELEASED DATE 5/9/01	REVISION DATE 5/18/01	REV. NO. A	SHEET 1 OF 1