

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

© COPYRIGHT BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.

LOC
ESDIST
-

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
B		REVISED PER ECR-10-011717	30MAY2010	S.W	S.Y

RECOMMENDED P.C. BOARD LAYOUT
P.C. BOARD THK 0.8~1.2
(VIEW FROM CONNECTOR MOUNTING SIDE)

NOTES

△ MATERIAL HOUSING : THERMOPLASTIC RESIN, UL94V-0
COLOR ; BLACK

CONTACT : COPPER ALLOY
RETENTION LEG : COPPER ALLOY

△ FINISH CONTACT : Ni ALL OVER UNDER PL
Pd-Ni PL. AT CONTACT AREA
Au FLASH PL. AT CONTACT AREA
TIN-LEAD PL. AT LEAD AREA
RETENTION LEG : TIN-LEAD PL.

1612413-1 ; AS SHOWN

A

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN
Y.WATANABE 21-JUN-'99CHK
K.ASAKAWA 21-JUN-'99APVD
I.ENOMOTO 22-JUN-'99PRODUCT SPEC
108-5599

APPLICATION SPEC

WEIGHT

CUSTOMER DRAWING

DIMENSIONS:
MM

MATERIAL
△TOLERANCES UNLESS
OTHERWISE SPECIFIED:

0-PLG	±	10	±0.2
1-PLG	±	30	>10 ±0.25
2-PLG	±	100	>30 ±0.3
3-PLG	±		
4-PLG	±		
ANGLES			±3°

FINISH

△

Tyco Electronics
Shanghai, P.R.China, 200233NAME
PLUG ASSEMBLY
2.5mm PITCH BATTERY CONNECTOR
5POS. OFFSET DIP TYPE

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A3	00779	C=1318790	-

SCALE 2:1 SHEET 1 OF 1 REV B

AMP 1470-19 REV 31MAR2000