

Passive module - UM-4SL/SPT/ADR541/CS/C-L - 2968548

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Interface module for the connection of the field side via spring-cage connection to the Yokogawa ADR 541 card. Fuse (5 x 20) with fuse failure display (LED) per channel. AKB 334 system connection to the controller.

The figure shows version UM-4SL/
SPT/ADR541/CS

RoHS

Key Commercial Data

Packing unit	1 STK
Weight per Piece (excluding packing)	727.000 g
Custom tariff number	85369010
Country of origin	Germany

Technical data

Note

Utilization restriction	EMC: class A product, see manufacturer's declaration in the download area
-------------------------	---

Dimensions

Width	232.5 mm
Height	126 mm
Depth	104 mm

Ambient conditions

Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C

General

Note	Voltage monitoring on the module does not work in combination with upstream HESILED fuse terminal blocks with integrated LED display.
Max. perm. operating voltage	24 V DC ±10 %

Passive module - UM-4SL/SPT/ADR541/CS/C-L - 2968548

Technical data

General

Max. perm. current (per branch)	630 mA
Max. permissible current (all branches)	6.3 A
Status display	Green LED
Mounting position	any
Assembly instructions	In rows with zero spacing
Standards/regulations	DIN EN 50178
Rated surge voltage	0.8 kV (basic insulation)
Degree of pollution	2
Overvoltage category	III

Connection data for connection 1

Connection name	Field level
Connection method	Spring-cage connection
Conductor cross section solid	0.2 mm ² ... 4 mm ²
Conductor cross section flexible	0.2 mm ² ... 25 mm ²
Conductor cross section AWG	24 ... 12
Number of positions	32

Connection data for connection 2

Connection name	Controller level
Connection method	COMBICON connectors
Number of connections	4
Number of positions	18
Note	Yokogawa AKB334-compatible

Supported controller

Controller	YOKOGAWA CS3000 CentumVP
- suitable I/O card	ADR541


Standards and Regulations

Standards/regulations	DIN EN 50178
Degree of pollution	2
Overvoltage category	III

Drawings


Passive module - UM-4SL/SPT/ADR541/CS/C-L - 2968548

Dimensional drawing



Passive module - UM-4SL/SPT/ADR541/CS/C-L - 2968548

Circuit diagram



Passive module - UM-4SL/SPT/ADR541/CS/C-L - 2968548

Classifications

eCl@ss

eCl@ss 4.0	27250313
eCl@ss 4.1	27250313
eCl@ss 5.0	27250313
eCl@ss 5.1	27250313
eCl@ss 6.0	27069203
eCl@ss 7.0	27069203
eCl@ss 8.0	27141152
eCl@ss 9.0	27141152

ETIM

ETIM 2.0	EC001437
ETIM 3.0	EC001437
ETIM 4.0	EC001437
ETIM 5.0	EC002780

UNSPSC

UNSPSC 6.01	30211824
UNSPSC 7.0901	39121421
UNSPSC 11	39121421
UNSPSC 12.01	39121421
UNSPSC 13.2	39121421