



REV.	DESCRIPTION	DATE
A	RELEASE	2012.11.12


NOTES:
 Insulator Material: PBT, UL 94V-0
 Contact Plating: Flash Gold
 Contact Material: Brass

Current Rating : 1A AC,DC
 Contact Resistance: 20MΩ Max.
 Dielectric Withstanding: AC 500V
 Insulator Resistance: 1000MΩ Min.
 Operating Temp.: -40°C~+105°C

NUMBER OF POSITIONS	DIMENSIONS	
	A	B
06	4.00	21.60
08	6.00	23.60
10	8.00	25.60
12	10.00	27.60
14	12.00	29.60
16	14.00	31.60
20	18.00	35.60
24	22.00	39.60
26	24.00	41.60
30	28.00	45.60
34	32.00	49.60
40	38.00	55.60
44	42.00	59.60
50	48.00	65.60
60	58.00	75.60



UNLESS TOLERANCE	
GENERAL	ANGLE
X. ± 0.30	X°. $\pm 3.0^\circ$
.X ± 0.20	.X° $\pm 2.0^\circ$
.XX ± 0.15	.XX° $\pm 1.0^\circ$
.XXX ± 0.08	.XXX° $\pm 0.5^\circ$



SCALE	SHEET	UNIT	DRAW NO.	REV.
1:1	1/1	MM	3110-XX-001-13-00	A

CnC Tech,LLC

Part No.

3110-XX-001-13-00