



Recommended Cable Stripping Dim's

NOTES: Finish (Plating Thickness in Micro-inches)  
 1. Brass  
 2. Nickel Pl. 100 Min. Thick over Copper Pl. 50 Min. Thick  
 3. Gold Pl. 3 Min Thick over Nickel Pl. 50 Min. Thick over Copper Pl. 50 Min. Thick  
 4. DELRIN

Crimped Ferrule  
 Hex Crimp Size .325 (8.3)  
 Crimped Contact Pin  
 Hex Crimp Size .068 (1.7)

RoHS Compliant

9	Ferrule	Note 1	Note 2	1	
8	Contact Pin	Note 1	Note 3	1	
7	Washer	Note 1	Note 2	1	
6	Spring	SK5	Note 2	1	
5	Retaining Ring	Note 1	Note 2	1	
4	Gasket	Rubber	Red	1	
3	Insulator	Note 4	Natural	1	
2	Body	Note 1	Note 2	1	
1	Shell	Note 1	Note 2	1	
No.	Description	Material	Finish	Q'ty	Drawing No.

Dimensions are in Inches  
 Unless Otherwise Specified  
 Tolerances  
 0.5-6 = ±0.2  
 6-30 = ±0.4  
 30-120 = ±0.6  
 120-315 = ±1  
 315-1000 = ±1.6  
 1000-2000 = ±2.4

Part No.	
Approved	Date 12-13-2010
Checked	Date 12-13-2010
Drawn	Date 12-13-2010

<b>NTE Electronics</b>	
Title	BNC Crimp Plug (For Belden 8281)
Drawing No.	06-B007
File No.	