

product type designation

product description



IWLAN Access Point

IWLAN access point, SCALANCE WAM763-1, 1 radio, 2.4/5 GHz, IEEE 802.11ax (Wi-Fi 6), 2 R-SMA connections, iFeatures support via CLP, 1201 Mbps (gross) 4x10/100/1000 Mbps RJ45 ports, redundant 24 V DC, terminal block, IP30, -30..+60°C, CLP slot, DI/DO, terminal block, observe national approvals! CERT ID: MSAX-W1-RJ-E2 FCC ID: LYHMSAXV1 operation outside of USA/Israel scope of delivery: cover CLP slot, covers antenna connections, 3x terminal block

transfer rate	
transfer rate	
<ul style="list-style-type: none"> with WLAN / maximum 	1201 Mbit/s
<ul style="list-style-type: none"> for Industrial Ethernet 	10, 100, 1000 Mbit/s
transfer rate / for Industrial Ethernet	
<ul style="list-style-type: none"> minimum 	10 Mbit/s
<ul style="list-style-type: none"> maximum 	1000 Mbit/s
interfaces	
number of electrical/optical connections / for gigabit Ethernet / maximum	4
number of electrical connections	
<ul style="list-style-type: none"> for network components or terminal equipment 	4
<ul style="list-style-type: none"> for power supply 	1
<ul style="list-style-type: none"> for redundant voltage supply 	1
type of electrical connection	
<ul style="list-style-type: none"> for network components or terminal equipment 	RJ45 socket
<ul style="list-style-type: none"> for power supply 	5-pole terminal block
design of the removable storage	
<ul style="list-style-type: none"> CLP 	Yes
<ul style="list-style-type: none"> CLP iFeatures 	Yes
memory	
design of the removable storage	
<ul style="list-style-type: none"> CLP 	Yes
<ul style="list-style-type: none"> CLP iFeatures 	Yes
interfaces / wireless	
number of radio cards / permanently installed	2
transmission mode / for multiple input multiple output (MIMO)	2x2
number of spatial streams	2
number of electrical connections / for external antenna(s)	2
type of electrical connection / for external antenna(s)	R-SMA (socket)
product feature / external antenna can be mounted directly on device	Yes
signal inputs/outputs	
number of digital inputs	1
number of digital outputs	1
type of electrical connection / at the digital inputs/outputs	2-pole terminal block in each case
signal range / at digital input	-30 V DC 30 V
signal range / at digital output	24 V / 0.5 A DC
operational current / of the signaling contacts / at DC / at 30 V /	0.008 A

maximum	
supply voltage, current consumption, power loss	
type of voltage / of the supply voltage	redundant power supply, 24 V DC, 5-pole terminal block
consumed current	
• at DC / at 24 V	0.55 A
• at DC / at 24 V / sleep mode / maximum	0.013 A
power loss [W]	
• at DC / at 24 V	13.2 W
• at DC / at 24 V / sleep mode / maximum	0.3 W
supply voltage / 1 / rated value	24 V
• type of voltage / 1 / of the supply voltage	DC
supply voltage / 2 / rated value	24 V
• type of voltage / 2 / of the supply voltage	DC
ambient conditions	
ambient temperature	
• during operation	-30 ... +60 °C
• during storage	-40 ... +85 °C
• during transport	-40 ... +85 °C
relative humidity / at 25 °C / without condensation / during operation / maximum	90 %
protection class IP	IP30
design, dimensions and weights	
width	35 mm
height	157 mm
depth	137 mm
width / of the enclosure / without antenna	35 mm
height / of the enclosure / without antenna	152.5 mm
depth / of the enclosure / without antenna	137 mm
net weight	0.65 kg
fastening method	wall mounting, DIN rail, mounting rail S7-300, mounting rail S7-1500, with adapter: 90° installation on DIN rail
• S7-300 rail mounting	Yes
• S7-1500 rail mounting	Yes
• 35 mm top hat DIN rail mounting	Yes
• wall mounting	Yes
radio frequencies	
operating frequency	
• for WLAN in 2.4 GHz frequency band	2.41 ... 2.48 GHz; depending on the country approvals
• for WLAN in 5 GHz frequency band	4.9 ... 5.8 GHz; depending on the country approvals
product features, product functions, product components / general	
product function / Access Point Mode	Yes
product function / client Mode	Yes
number of SSIDs	8
product function	
• iPCF Access Point	No
• iPCF-2 access point	Yes; iPCF-2 is not compatible with iPCF. See documentation for function description.
• iPCF client	No
• iPCF-2 client	Yes; iPCF-2 is not compatible with iPCF. See documentation for function description.
product function / iPRP	Yes
product functions / management, configuration, engineering	
number of manageable IP addresses / in client	2
product function	
• CLI	Yes
• web-based management	Yes
• MIB support	Yes
• TRAPs via email	Yes
• configuration with STEP 7	Yes
• configuration with STEP 7 in the TIA Portal	Yes
• WDS	No
protocol / is supported	

<ul style="list-style-type: none"> • Address Resolution Protocol (ARP) 	Yes
<ul style="list-style-type: none"> • ICMP 	Yes
<ul style="list-style-type: none"> • Telnet 	Yes
<ul style="list-style-type: none"> • HTTP 	Yes
<ul style="list-style-type: none"> • HTTPS 	Yes
<ul style="list-style-type: none"> • TFTP 	Yes
<ul style="list-style-type: none"> • DCP 	Yes
<ul style="list-style-type: none"> • LLDP 	Yes
identification & maintenance function	
<ul style="list-style-type: none"> • I&M0 - device-specific information 	Yes
<ul style="list-style-type: none"> • I&M1 - higher level designation/location designation 	Yes
product functions / diagnostics	
product function	
<ul style="list-style-type: none"> • PROFINET IO diagnosis 	Yes
<ul style="list-style-type: none"> • SysLog 	Yes
protocol / is supported	
<ul style="list-style-type: none"> • SNMP v1 	Yes
<ul style="list-style-type: none"> • SNMP v2 	Yes
<ul style="list-style-type: none"> • SNMP v3 	Yes
product functions / VLAN	
product function	
<ul style="list-style-type: none"> • function VLAN with IWLAN 	Yes
number of VLANs / maximum	24
product functions / DHCP	
product function	
<ul style="list-style-type: none"> • DHCP client 	Yes
product functions / redundancy	
protocol / is supported	
<ul style="list-style-type: none"> • STP/RSTP 	Yes
<ul style="list-style-type: none"> • MSTP 	Yes
<ul style="list-style-type: none"> • RSTP 	Yes
product function	
<ul style="list-style-type: none"> • redundancy procedure MSTP 	Yes
product functions / security	
product function	
<ul style="list-style-type: none"> • management security, ACL-IP based 	No
<ul style="list-style-type: none"> • IEEE 802.1x (radius) 	Yes
<ul style="list-style-type: none"> • NAT/NAPT 	Yes
<ul style="list-style-type: none"> • access protection according to IEEE802.11i 	Yes
<ul style="list-style-type: none"> • WPA/WPA2 	Yes
<ul style="list-style-type: none"> • WPA3 	Yes
<ul style="list-style-type: none"> • TKIP/AES 	Yes
<ul style="list-style-type: none"> • RADIUS client 	Yes
protocol / is supported	
<ul style="list-style-type: none"> • SSH 	Yes
key length	
<ul style="list-style-type: none"> • with SSL 	4096 bit
product functions / time	
protocol / is supported	
<ul style="list-style-type: none"> • NTP 	Yes
<ul style="list-style-type: none"> • SNTP 	Yes
<ul style="list-style-type: none"> • SIMATIC time synchronization (SIMATIC Time) 	Yes
standards, specifications, approvals	
certificate of suitability	
<ul style="list-style-type: none"> • EC Declaration of Conformity 	Yes
<ul style="list-style-type: none"> • CE marking 	Yes
standard for wireless communication	
<ul style="list-style-type: none"> • IEEE 802.11a 	Yes
<ul style="list-style-type: none"> • IEEE 802.11b 	Yes
<ul style="list-style-type: none"> • IEEE 802.11e 	Yes

<ul style="list-style-type: none"> • IEEE 802.11g • IEEE 802.11h • IEEE 802.11i • IEEE 802.11n • IEEE 802.11ac • IEEE 802.11ax • IEEE 802.11r 	<p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p>
MTBF	26 a
<ul style="list-style-type: none"> • reference temperature 	40 °C
further information / internet links	
internet link	
<ul style="list-style-type: none"> • to website: TIA Selection Tool • to web page: selection aid TIA Selection Tool • to the website: IWLAN • to website: Industry Mall • to website: Information and Download Center • to website: Image database • to website: CAx-Download-Manager • to website: Industry Online Support 	<p>http://www.siemens.com/tia-selection-tool</p> <p>http://www.siemens.com/tia-selection-tool</p> <p>http://www.siemens.com/iwlan</p> <p>https://mall.industry.siemens.com</p> <p>http://www.siemens.com/industry/infocenter</p> <p>http://automation.siemens.com/bilddb</p> <p>http://www.siemens.com/cax</p> <p>https://support.industry.siemens.com</p>
security information	
security information	<p>Siemens provides products and solutions with industrial security functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial security concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial security measures that may be implemented, please visit https://www.siemens.com/industrialsecurity. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Security RSS Feed under https://www.siemens.com/cert. (V4.6)</p>

last modified:

7/11/2023 