




# CYLINDRICAL HOUSED LINEAR VOICE COIL ACTUATORS (VCA)

## Introduction

A fully housed voice coil actuator (VCA) further expands upon the idea of the semi-housed VCA, incorporating the self-aligning bushings and shaft, but fully captures the coil assembly to keep it concentric with the field assembly, adds an internal flex circuit to protect external moving wires and also limits the axial travel on both ends of the stroke.

As a single piece, the linear actuator can be mounted on one side and does not require a customer supplied alignment system, making it easy to integrate into applications. Housed voice coil actuators feature all of the inherent advantages of VCA technology, such as direct-drive, zero backlash and cog free operation for accurate motion, as well as high acceleration and use of single phase.



## Features

- Designs available with magnet springs and/or latches
- Different shaft options available
- Housing offers additional mechanical and environmental protection
- Single unit that is more easily integrated into customer applications
- Life tested in excess of 500 million cycles



## CYLINDRICAL HOUSED LINEAR VOICE COIL ACTUATOR (VCA) CONFIGURATIONS

Part Number	Peak Force (N / lb)	Total Stroke (mm / in)	Continuous Stall Force (N / lb)	Actuator Constant (N $\sqrt{\text{watt}}$ / lb $\sqrt{\text{watt}}$ )	Outside Diameter/Width (mm / in)	Length at Mid-stroke (mm / in)
LAH04-10-000A	1.89 / 0.42	4.00 / 0.16	1.11 / 0.25	0.84 / 0.19	10.1 / 0.40	25.4 / 1.00
LAH13-18-000A-3E	15.5 / 3.50	6.36 / 0.25	5.07 / 1.14	2.36 / 0.53	31.6 / 1.24	45.7 / 1.80
LAH13-18-000A-3S	15.5 / 3.50	6.36 / 0.25	5.07 / 1.14	2.36 / 0.53	31.6 / 1.24	45.7 / 1.80
LAH16-23-000A-4E	89.0 / 20.0	6.08 / 0.24	17.0 / 3.82	5.83 / 1.31	40.0 / 1.57	58.4 / 2.30
LAH16-23-000A-4S	89.0 / 20.0	6.08 / 0.24	17.0 / 3.82	5.83 / 1.31	40.0 / 1.57	58.4 / 2.30
LAH28-53-000A-12E	266 / 60.0	25.0 / 0.98	60.1 / 13.5	13.0 / 2.94	70.0 / 2.76	132 / 5.22
LAH28-53-000A-12I	266 / 60.0	25.0 / 0.98	60.1 / 13.5	13.0 / 2.94	70.0 / 2.76	132 / 5.22
LAH28-53-000A-12S	266 / 60.0	25.0 / 0.98	60.1 / 13.5	13.0 / 2.94	70.0 / 2.76	132 / 5.22
LAH43-86-001Z	1512 / 340	31.7 / 1.25	386 / 86.9	38.3 / 8.61	218 / 8.60	108 / 4.25

Sensata Technologies, Inc. ("Sensata") data sheets are solely intended to assist designers ("Buyers") who are developing systems that incorporate Sensata products (also referred to herein as "components"). Buyer understands and agrees that Buyer remains responsible for using its independent analysis, evaluation and judgment in designing Buyer's systems and products. Sensata data sheets have been created using standard laboratory conditions and engineering practices. Sensata has not conducted any testing other than that specifically described in the published documentation for a particular data sheet. Sensata may make corrections, enhancements, improvements and other changes to its data sheets or components without notice.

Buyers are authorized to use Sensata data sheets with the Sensata component(s) identified in each particular data sheet. HOWEVER, NO OTHER LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE TO ANY OTHER SENSATA INTELLECTUAL PROPERTY RIGHT, AND NO LICENSE TO ANY THIRD PARTY TECHNOLOGY OR INTELLECTUAL PROPERTY RIGHT, IS GRANTED HEREIN. SENSATA DATA SHEETS ARE PROVIDED "AS IS". SENSATA MAKES NO WARRANTIES OR REPRESENTATIONS WITH REGARD TO THE DATA SHEETS OR USE OF THE DATA SHEETS, EXPRESS, IMPLIED OR STATUTORY, INCLUDING ACCURACY OR COMPLETENESS. SENSATA DISCLAIMS ANY WARRANTY OF TITLE AND ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, QUIET ENJOYMENT, QUIET POSSESSION, AND NON-INFRINGEMENT OF ANY THIRD PARTY INTELLECTUAL PROPERTY RIGHTS WITH REGARD TO SENSATA DATA SHEETS OR USE THEREOF.

All products are sold subject to Sensata's terms and conditions of sale supplied at [www.sensata.com](http://www.sensata.com) SENSATA ASSUMES NO LIABILITY FOR APPLICATIONS ASSISTANCE OR THE DESIGN OF BUYERS' PRODUCTS. BUYER ACKNOWLEDGES AND AGREES THAT IT IS SOLELY RESPONSIBLE FOR COMPLIANCE WITH ALL LEGAL, REGULATORY AND SAFETY-RELATED REQUIREMENTS CONCERNING ITS PRODUCTS, AND ANY USE OF SENSATA COMPONENTS IN ITS APPLICATIONS, NOTWITHSTANDING ANY APPLICATIONS-RELATED INFORMATION OR SUPPORT THAT MAY BE PROVIDED BY SENSATA.

Mailing Address: Sensata Technologies, Inc., 529 Pleasant Street, Attleboro, MA 02703, USA.

## CONTACT US

### Americas

+1 (760) 597 7042  
sales.beikimco@sensata.com **E**  
**urope, Middle East & Africa**  
+1 (760) 597 7042  
support@sensata.com

### Asia Pacific

sales.isasia@list.sensata.com **C**  
hina +86 (21) 2306 1500 Japan  
+81 (45) 277 7117 Korea +82  
(31) 601 2004 India +91 (80)  
67920890  
Rest of Asia +603-5566 6001