THT male header; $1.0 \times 1.0 \text{ mm}$ solder pin; straight; Pin spacing 5 mm; 8-pole; gray



www.wago.com/769-638



Data Electrical data

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG Hansastr. 27 32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169 Email: info.de@wago.com | Web: www.wago.com

www.wago.com/769-638



Ratings per IEC/EN

| Nominal voltage (III/3) | 250 V |
|-------------------------------|---|
| Rated impulse voltage (III/3) | 4 kV |
| Rated voltage (III/2) | 500 V |
| Rated impulse voltage (III/2) | 4 kV |
| Rated current | 32 A |
| Legend (ratings) | (III / 3) ≙ Overvoltage category III / Pollution degree 3 |

Connection data

| Total number of potentials | 8 |
|----------------------------|----|
| Number of levels | 1 |
| Preceding contacts | No |

Connection 1

| Pole number | 0 | |
|---------------|---|--|
| FOIE HUITIDEI | 0 | |

Physical data

| Pin spacing | 5 mm / 0.197 inches |
|-------------------------|------------------------|
| Width | 43.6 mm / 1.717 inches |
| Height from the surface | 22.2 mm / 0.874 inches |
| Depth | 18.3 mm / 0.72 inches |

Mechanical Data

| Variable coding | Yes |
|--------------------------|-----|
| Mounting type | PCB |
| Anti-rotation protection | Yes |

Plug-in connection

| Contact type (pluggable connector) | Male connector/plug |
|--------------------------------------|---------------------|
| Connector (connection type) | for PCB |
| Mismating protection | No |
| Plugging without loss of pin spacing | No |
| Mating direction to the PCB | 90 ° |

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG

Hansastr. 27 32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169 Email: info.de@wago.com | Web: www.wago.com

www.wago.com/769-638



PCB contact

PCB contact THT

Material Data

Note (material data)

Information on material specifications can be found here

| Color | gray |
|-----------------------------|------------------|
| Material group | ı |
| Insulation material | Polyamide (PA66) |
| Flammability class per UL94 | V0 |
| Fire load | 0.219 MJ |
| Weight | 8.2 g |

Environmental requirements

| Processing temperature | -35 +85 ℃ |
|----------------------------------|-------------|
| Continuous operating temperature | -60 +105 °C |

Commercial data

| Product Group | 18 (X-COM-System) |
|-----------------------|-------------------|
| eCl@ss 10.0 | 27-44-04-02 |
| eCl@ss 9.0 | 27-44-04-02 |
| ETIM 8.0 | EC002637 |
| ETIM 7.0 | EC002637 |
| PU (SPU) | 25 pcs |
| Packaging type | box |
| Country of origin | PL |
| GTIN | 4044918270717 |
| Customs tariff number | 85366930000 |

Environmental Product Compliance

| RoHS Compliance Status | Compliant,No Exemption | |
|------------------------|------------------------|--|

Approvals / Certificates

General approvals

 $\label{thm:continuity} \textbf{Subject to changes. Please also observe the further product documentation!}$

WAGO GmbH & Co. KG Hansastr. 27

32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169 Email: info.de@wago.com | Web: www.wago.com Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.

www.wago.com/769-638



| Logo | Approval | Additional Approval Text | Certificate name |
|--|--|--------------------------|------------------|
| | CCA DEKRA Certification B.V. | EN 60947 | NTR NL- 7626 |
| | CCA DEKRA Certification B.V. | IEC 61984 | NL-47799 /A1 |
| | CCA DEKRA Certification B.V. | EN 61984 | 2190419.02 |
| | CSA CSA Group | C22.2 | 1101144 |
| | KEMA/KEUR DEKRA Certification B.V. | EN 60947 | 2190419.01 |
| | UL Underwriters Laboratories Inc. | UL 1977 | E 45171 |
| | UR Underwriters Laboratories Inc. | UL 1059 | E45172 |
| Declaration | ns of conformity and manufacturer's declarations | | |
| Logo | Approval | Additional Approval Text | Certificate name |
| EU-Declaration of Conformity WAGO GmbH & Co. KG UK-Declaration of Conformity WAGO GmbH & Co. KG | | - | - |
| | - | - | - |
| Approvals f | for marine applications | | |
| Logo | Approval | Additional Approval Text | Certificate name |
| | DNV GL Det Norske Veritas, Germanischer Lloyd | - | TAE00001V2 |

Optional accessories

Marking accessories

| Marking accessories | |
|---|----------------------|
| Marking strip | |
| Item no.: 210-831 Marking strips; on reel; 2.3 mm wide; plain; Self-adhesive; white | www.wago.com/210-831 |
| Item no.: 210-833 Marking strips; 25 m on roll; 6 mm wide; plain; Self-adhesive; white | www.wago.com/210-833 |
| Item no.: 210-834 Marking strips; on reel; 5 mm wide; plain; Self-adhesive; white | www.wago.com/210-834 |

 $\label{thm:condition} \textbf{Subject to changes. Please also observe the further product documentation!}$

WAGO GmbH & Co. KG

Hansastr. 27 32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169 Email: info.de@wago.com | Web: www.wago.com

www.wago.com/769-638



Item no.: 210-832

Marking strips; on reel; 3 mm wide; plain; Self-adhesive; white

www.wago.com/210-832

Coding

Item no.: 769-435

Coding pin; for coding of female plugs; for carrier terminal blocks / male connectors; orange

www.wago.com/769-435

URL

Downloads

Documentation

Bid Text

| 769-638 X81 - Datei | 2019 年2月19日 | xml 3.0 kB | Download |
|------------------------|--------------|----------------|----------|
| 769-638 doc - Datei | 2017 年10 月4日 | doc 25.6 kB | Download |
| Additional Information | | pdf 2.2 MB | Download |

CAD/CAE-Data

CAD data

2D/3D Models 769-638 URL Download

PCB Design

Symbol and Footprint 769-638

CAx data for your PCB design, consisting of "schematic symbols and PCB footprints",

allow easy integration of the WAGO component into your development environment.

Supported formats:

- Accel EDA 14 & 15
- Altium 6 to current version
- Cadence Allegro
- DesignSpark
- Eagle Libraries
- KiCad
- Mentor Graphics BoardStation

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG

Hansastr. 27 32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169 Email: info.de@wago.com | Web: www.wago.com Do you have any questions about our products? We are always happy to take your call at +49 (571) 887-44222.

01.09.2023 Page 5/8

Download

www.wago.com/769-638



- Mentor Graphics Design Architect
- Mentor Graphics Design Expedition 99 and 2000
- OrCAD 9.X PCB and Capture
- PADS PowerPCB 3, 3.5, 4.X, and 5.X
- PADS PowerPCB and PowerLogic 3.0
- PCAD 2000, 2001, 2002, 2004, and 2006
- Pulsonix 8.5 or newer
- STL
- 3D STEP
- TARGET 3001!
- View Logic ViewDraw
- Quadcept
- Zuken CadStar 3 and 4
- Zuken CR-5000 and CR-8000

PCB Component Libraries (EDA), PCB CAD Library Ultra Librarian

CAE data

ZUKEN Portal 769-638 URL Download

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 769-638 URL Download

THT male header; 1.0 x 1.0 mm solder pin; straight; Pin spacing 5 mm; 8-pole; gray

Installation Notes

Installation

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG Hansastr. 27 32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169 Email: info.de@wago.com | Web: www.wago.com

www.wago.com/769-638



| | 7 |
|--|--|
| | |
| | |
| | |
| | |
| | |
| Cutout | |
| Male headers with solder pins | |
| Application | |
| | |
| | |
| | |
| | |
| | |
| | |
| Male headers with straight solder pins and 1-conductor female plugs (picture shows a relay | Male headers with solder pins for printed circuit boards |
| module) | |
| | 7 |
| | |
| | |
| | |
| | |
| | |
| Pluggable PCB connection | Male headers with solder pins |
| Connection to a relay module inside the switchgear cabinet | Integrating PCB components into the system wiring. |
| Product family | |
| Subject to changes Places also observe the | jurther product documentation! |
| Subject to changes. Please also observe the f | urther product documentation! |

WAGO GmbH & Co. KG Hansastr. 27

32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169 Email: info.de@wago.com | Web: www.wago.com

www.wago.com/769-638



х-сом

Show all products from the family

 $\label{thm:condition} \textbf{Subject to changes. Please also observe the further product documentation!}$

Phone: +49571 887-0 | Fax: +49571 887-169 Email: info.de@wago.com | Web: www.wago.com