

6

5

4

3

2

1

D

D

C


C

B

B

A

A



SHELL	SHELL	SHIELDING	BRAID WIRE
4	5	GROUND	BLACK
3	3	+DATA	GREEN
2	2	-DATA	WHITE
1	1	VCC	RED
P 1	P 2	SIGNAL NAME	WIRE COLOR

ITEM	DESCRIPTION	L	QTY.
L	COPPER FOIL 887801083		1
K	COPPER FOIL 887801114		1
J	USB SERIES MINI-B PLG COVER SHIELD 675460000		1
H	USB SERIES MINI-B PLG SHIELD CASE 675450000		1
G	MINI-B PLG HSG&TERMINAL SUB-ASS'Y 675420008		1
F	TERMINAL (AWG24) (SEE TABLE)		2
E	TERMINAL (AWG28) (SEE TABLE)		2
D	USB2.0 #28/#24 ; CABLE(SEE TABLE)		
C	REAR SHELL 887809084		1
B	FRONT SHELL 887809083		1
A	CRIMP HOUSING 887809086		1

WIRE DIAGRAM

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

DIMENSION UNITS		SCALE		CURRENT REV DESC: OBSOLETE PART NUMBER							
mm		NTS									
GENERAL TOLERANCES (UNLESS SPECIFIED)				EC NO: 628958		USB2.0, A TO MINIB CABLE ASSY PRODUCT CUSTOMER DRAWING					
				DRWN: AKUMAR19 2019/12/17							
				CHK'D: GGA 2020/01/16		DOCUMENT NUMBER: SD-887328500 DOC TYPE: PSD DOC PART: 001 REVISION: B					
				APPR: GGA 2020/01/16							
				INITIAL REVISION:		MATERIAL NUMBER: 887-328x-0x CUSTOMER: GENERAL MARKET SHEET NUMBER: 1 OF 2					
				DRWN: JFZHENG 2006/01/07							
				APPR: DQLUO 2006/01/07							
ANGULAR TOL ± 0.5 °				DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIRD ANGLE PROJECTION		DRAWING: A4-SIZE		SERIES: 88732	

DOCUMENT STATUS	P1	RELEASE DATE	2020/01/16	06:07:10
-----------------	----	--------------	------------	----------

6

5

4

3

2

1

NOTE:

1. MOLDED PVC RESIN.CABLE P/N & COLOR AS TABLE

WHITE	887800043	887808233	WHITE
BEIGE	887800059	887808244	BEIGE
BLACK	887800019	887808563	BLACK
BLACK	887800019	887808236	BLACK
BLACK	887800019	887808248	BLACK
FROST WITHE	887800043	887808243	FROST WITHE
RESIN COLOR	RESIN P/N	CABLE P/N	CABLE COLOR

2. STICK UL LABEL ON EACH CARTON.

ELECTRICAL PERFORMANCE:

ALL TEST DUABILITY:0.01 SEC.

1. DIELECTRONIC STRENGTH:500V DC

2. INSULATION RESISTANCE:100M OHMS MIN.

3. CONDUCTIVE RESISTANCE: 3 OHMS MAX.

3. PUT COC AND INSPECTION REPORT IN EVERY CARTON (ONLY APPLY FOR 887328705)

4.ALL COMPONENTS MUST MEET RoHS COMPLIANCE

TABLE

88732-8902	2000±30	USB_A TO MINI_B 2.0 VER	88780-8248	88780-9091	88780-9090
88732-8802	1800±30	USB_A TO MINI_B 2.0 VER	88780-8248	88780-9091	88780-9090
88732-8702	1500±30	USB_A TO MINI_B 2.0 VER	88780-8248	88780-9091	88780-9090
88732-8602	1000±30	USB_A TO MINI_B 2.0 VER	88780-8248	88794-1218	88794-1217
88732-8502	800±30	USB_A TO MINI_B 2.0 VER	88780-8235	88794-1218	88794-1217
88732-8900	2000±30	USB_A TO MINI_B 2.0 VER	88780-8243	88780-9091	88780-9090
88732-8800	1800±30	USB_A TO MINI_B 2.0 VER	88780-8243	88780-9091	88780-9090
88732-8600	1000±30	USB_A TO MINI_B 2.0 VER	88780-8243	88794-1218	88794-1217
88732-8500	800±30	USB_A TO MINI_B 2.0 VER	88780-8233	88794-1218	88794-1217
88732-8401	1200±30	USB_A TO MINI_B 2.0 VER	88780-8244	88780-9091	88780-9090
MX P/N	CABLE LENGTH	DESCRIPTION	CABLE P/N	TERM. E P/N	TERM. F P/N

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION										
DIMENSION UNITS		SCALE		CURRENT REV DESC: OBSOLETE PART NUMBER			molex			
mm		NTS		NUMBER						
GENERAL TOLERANCES (UNLESS SPECIFIED)				EC NO: 628958			USB2.0, A TO MINIB CABLE ASSY			
		MM	INCH	DRWN: AKUMAR19 2019/12/17						
4 PLACES		±	±	CHK'D: GGA 2020/01/16			PRODUCT CUSTOMER DRAWING			
3 PLACES		±	±	APPR: GGA 2020/01/16						
2 PLACES		±	±	INITIAL REVISION:			DOCUMENT NUMBER			
1 PLACE		±	±	DRWN: JFZHENG 2006/01/07						
0 PLACES		±	±	APPR: DQLUO 2006/01/07			SD-887328500		DOC TYPE	REVISION
ANGULAR TOL ± 0.5 °				DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS			PSD 001		B	
THIRD ANGLE PROJECTION				DRAWING		SERIES		MATERIAL NUMBER		SHEET NUMBER
				A4-SIZE		88732		887-328x-0x		GENERAL MARKET
2 OF 2										

DOCUMENT STATUS P1 RELEASE DATE 2020/01/16 06:07:10

FORMAT: Met-lega-master-ib-prod-A4
REVISION: D
DATE: 2018/01/18

6

5

4

3

2

1