



Recommended Cable Stripping Dim's

NOTES: Finish (Plating Thickness in Micro-inches)
 1. Brass
 2. Nickel Pl. 100 Min. Thick over Copper Pl. 50 Min. Thick
 3. Phosphor Bronze
 4. Gold Pl. 3 Min Thick over Nickel Pl. 50 Min. Thick over Copper Pl. 50 Min. Thick
 5. Teflon

Crimped Ferrule
 Hex Crimp Size .213 (5.41)
 Crimped Contact Pin
 Hex Crimp Size .068 (1.7)

RoHS Compliant

10	Ferrule	Copper	Note 2	1	
9	Contact Pin	Note 3	Note 4	1	
8	Shell	Note 1	Note 2	1	
7	Gasket	Rubber	Red	1	
6	Retainer Ring	Note 1	Note 2	1	
5	Ring	DELTRIN	Natural	1	
4	Washer	Note 1	Note 2	1	
3	Barrel	Note 1	Note 2	1	
2	Insulator	Note 5	Natural	1	
1	Body	Note 1	Note 2	1	
No	Description	Material	Finish	Q'ty	Drawing No.

Dimensions are in Inches
 Unless Otherwise Specified
 Tolerances
 0.5-6 = ±0.2
 6-30 = ±0.4
 30-120 = ±0.6
 120-315 = ±1
 315-1000 = ±1.6
 1000-2000 = ±2.4

Part No.	
Approved	Date 6-6-2013
Checked	Date 6-6-2013
Drawn	Date 6-6-2013

NTE Electronics	
Title	TNC Reverse Polarity Crimp Plug (For RG-58C/U, 58U)
Drawing No.	06-T004
File No.	