Mallory Sonalert Products, Inc.				Part #: JT120-G-CDL			
Sa	les Outline	Drawing		Revision:		D	
Chasifications							
Specifications: Stack Number:	1 4	1	-			1	
LED Color:	GREEN						
Connection Wires:	Green and Brown						
LED Current Draw:	<190 mA						
Rated Voltage:	<130 IIIA	ļ.	120 VAC	ļ		<u> </u>	
Operating Voltage:	90-120 VAC						
Sound Level Category:	Loud	Loud	Loud				
	Loud	Medium Pulse		Loud			
Mode of Operation:	Continuous	(5PPS)	Double Pulse (0.		Continuous	Continuous for 5 sec then 0.1s beep until reset	
Connection:	Black and Gray Wires	Black and Gray Wires; Orange wire connected to	Black and Gray Wire wire connected to Gray wire	roon/Vollow Diack and		Gray wires; Orange and Purple nected to Green/Yellow wire	
Sound Current Draw:	40mA Max.	40mA Max.	40mA Max	40mA Max.		40mA Max.	
Loudness @ 1m:			80-85 dB(A) Ty				
Frequency:	2000 ± 500 Hz						
Total Max Current:	<230mA with all LED's and sound unit working						
Operating Temperature:	-25° ~ +60°C						
Lens Color:	Opaque White						
Material:	ABS FR15U						
Mounting Method:	Direct Mount using 1/2" NPT Stainless Steel Pipe and Nut						
Weight Typical (g):	275						
NEMA 12:	Approved						
Options:	Please contact factory.						
Dimensions: Inches (mm) CUL Recognized ROHS Compliant							
3.7 [94.1]		48" wire					
2.7 [68.3] TOP VIEW	Ø0.88 [Ø2 KNDCK E FDR WIF 2.4 [61.8]	IUT 🥄 _					
LED OPERATION: CONNEC	T STACK COLOR WIR	E TO POWER AND BE	ROWN WIRE TO POW	ER.			
SOUND OPERATION:	CONNECT GRAY AN	D BI ACK WIRES TO	POWER FOR CONTIN	IUOUS SOI	JND.		
FOR MEDIUM PULSE, CONNECT GRAY & BLACK TO POWER AND ORANGE WIRE TO GREEN/YELLOW WIRE.							
FOR DOUBLE PULSE, CONNECT GRAY & BLACK TO POWER AND PURPLE WIRE TO GREEN/YELLOW WIRE.							
						O GREEN/YELLOW WIRE.	
	. OIL OOM I/DEEL , O	C VECT GITAT & DEF	IOI TO FOWEITAIND	OT IT II VOL 0	. OIN LE IV	C C. ILLIVILLEOVV VVIIIL.	