



**Material**

Item a Clamp: Brass (CuZn), Ni plated  
 Item b Terminal screw: Steel Zinc plating "-" slot type  
 Item c Female contact : PhBz Tin plated  
 Item d Terminal (housing): Thermoplastic (UL94V-0)  
 Green(RAL6018/T)

**Electrical** cULus  
 Voltage rating: 300VAC  
 Current rating: 10A  
 Wire range:  
 Solid wire(AWG): 16-28  
 Stranded wire(AWG): 16-28  
 Torque(Lb-in): 1,7  
 Screw: M2  
 Wire strip length: 5-6mm  
 Withstanding Voltage: 1,6KV  
 Operating temperature: -40°C to +115°C  
 Safety Approval: **UL**

**DIMENSION**

L	Nx3.5
P	(N-1)x3.5

N=Number of poles

Poles	Tolerance	
	DIM L	DIM P
2p-6p	±0.15	±0.15
7p-12p	±0.20	±0.20
13p-18p	±0.25	±0.25
19p-24p	±0.30	±0.30

**RoHS compliant**  
 Unit: mm



Scale	Free TOLERANCE	Free TOL	Id.	Modification	Date	Name
X.	±0.50				14.06.2007	Alex
X.X	±0.30				18.04.2016	Amy
X.XX	±0.10		③	Add UL	18.04.2016	Amy
DIM	TOL		②	Update	20.04.2010	Alex
X.°	±1°		①	Drawn	14.06.2007	Hellwig
Angle	TOL					



Customer-No. \_\_\_\_\_

ASSMANN WSW-No. \_\_\_\_\_

Drawing-No. \_\_\_\_\_

**A-TB350-TTXX**

ASS 2251 CO rev03

Replace \_\_\_\_\_ Sheet \_\_\_\_\_

1	2	3	4	5	6	7	A
1	2	3	4	5	6	7	A
1	2	3	4	5	6	7	B
1	2	3	4	5	6	7	C
1	2	3	4	5	6	7	D
1	2	3	4	5	6	7	E
1	2	3	4	5	6	7	F
1	2	3	4	5	6	7	G
1	2	3	4	5	6	7	H