Data sheet 3450.8 FQI 1,5/10 YE





Insulated cross-connector, No. of poles: 10, Mounting type: Plug in, Width: 40.9 mm, Colour: Yellow

RAL: 1026

Business data

<u>3450.8</u>
FQI 1,5/10 YE
4044211110635
10
PC
5.2 g
5.3 g
G
85389099
CZ
3450.8
Insulated cross-connector

Data sheet





Tankaisal data		
Technical data		
Dimensions		
Length	4 mm	
Width	40.9 mm	
Pitch size	4.1 mm	
Ratings		
Max. voltage	800 V	
Rated current	17.5 A	
Current load, max.	17,5 A	
Rated cross-section	1.5 mm²	
Connection data		
No. of poles	10	
Materials		
Material	Copper	
Surface	Tin-nickel	
Insulation housing	Polyamide 6.6	
Flammability class UL 94	V-2	
Working temperature, min.	-40 °C	
Working temperature, max.	105 °C	
Further technical data		
Mounting type	Plug in	
Insulation available	✓	
Touch protection is available	✓	
Number of bridged terminals	10	
Environmental Product Compliance		
REACH Conform	Yes	_
REACH Candidate Substance Note	No	
RoHS Conform	Yes	

Data sheet 3450.8 FQI 1,5/10 YE



Media

Data sheet

3450.8 FQI 1,5/10 YE



Accessories

##INVERSE##CONTA-CONNECT



Feed-through terminal, Push-in connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 1.5 mm², Width: 4.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
3202.2	FRK 1,5/4A BG	4044211109684	100



Feed-through terminal, Push-in connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 1.5 mm², Width: 4.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
3200.2	FRK 1,5/2A BG	4044211109530	100



Feed-through terminal, Push-in connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 1.5 mm², Width: 4.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
3201.2	FRK 1,5/3A BG	4044211109615	100

##INVERSE##CONTA-CONNECT



Feed-through terminal, Push-in connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 1.5 mm², Width: 4.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
3201.2	FRK 1,5/3A BG	4044211109615	100