



Sealing plug for unused round control points, 22 mm, plastic, black, Z=100-unit packaging

| | |
|--|--|
| product brand name | SIRIUS ACT |
| product designation | Sealing plug |
| product type designation | 3SU1 |
| Actuator | |
| shape of the actuating element | round |
| outer diameter of the actuating element | 29.5 mm |
| General technical data | |
| protection class IP | IP66, IP67, IP69(IP69K) |
| degree of protection NEMA rating | 1, 2, 3, 3R, 4, 4X, 12 |
| reference code according to IEC 81346-2 | S |
| Substance Prohibition (Date) | 10/01/2014 |
| Ambient conditions | |
| ambient temperature | |
| • during operation | 70 ... -25 °C |
| • during storage and transport | -40 ... +80 °C |
| environmental category during operation according to IEC 60721 | 3M6, 3S2, 3B2, 3C3, 3K6 (with relative air humidity of 10 ... 95%) |
| Installation/ mounting/ dimensions | |
| shape of the installation opening | round |
| mounting diameter | 22.3 mm |
| positive tolerance of installation diameter | 0.4 mm |
| mounting height | 6.5 mm |
| installation width | 29.5 mm |
| installation depth | 24.2 mm |
| Accessories | |
| material of accessory | Plastic |
| color of accessory | black |
| Certificates/ approvals | |
| Further information | |

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SU1900-0FA10-0AA0-Z X90>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SU1900-0FA10-0AA0-Z X90>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3SU1900-0FA10-0AA0-Z X90>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SU1900-0FA10-0AA0-Z X90&lang=en

last modified:

4/4/2022 