

5. MATING PART: AT06-08SA* PLUG. (* = MODIFICATIONS AND COLORS)

4.7 RoHS COMPLIANT

6. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.

MILLIAMPS CURRENT LEAKAGE @ 1500 VOLTS AC. 4.4 INSULATION RESISTANCE: 1000 MEGOHMS MIN @ 25°C.

4.5 MOISTURE RESISTANCE: IP67 (MATED CONDITION)
4.6 MATING CYCLE DURABILITY: 100 CYCLES

7 CONTACT SIZE AND REAR SEAL WIRE RANGE:

CONTACT	MIN. INSUL	MAX. INSUL	TYPICAL
SIZE	O.D.	O.D.	WIRE RANGE
16	2.24 mm (.088 in)	3.68 mm (.145 in)	14 - 20 AWG

	PART N	NUMBER		DESCRIPTION		
QUANTITY		MA	TERI	ALS LIST		
UNLESS OTHERWISE SPECIFIED		SIGNATUR	ES DATE	A man b a mal		
1) All dimensions are in metric(mm). 2) Tolerances are as follows: 1 PL DEC ±0.30 Fractions ±1/64		DRAWN: BEOOK	30/NOV/18	Amphenol		
2 PL DEC ±0.15 3 PL DEC ±0.08	Angles ±1°	CHECKED: ORION	30/NOV/18	Sine Systems - www.amphenol-sine.com	_	
3) Note reference = X		ENGINEER:		44724 Morley Drive Clinton Township, MI 48036		
MATERIAL SPECIFICA	TIONS:	APPROVAL: TOMM	30/NOV/18	Clinton Township, MI 48036		
		CUSTOMER:	•	8P RECEPTACLE, FLANGE MOUNT, BLACK, END CA	P	
PROCESS SPECIFICATIONS: NEXT ASSY:		THIS DRAWING IS SUPP INFORMATION ONLY. DE	SIGN FEATURES,			
		SPECIFICATIONS AND P SHOWN HEREON ARE T THE AMPHENOL CORPO OF REPRODUCTION ARE DIMENSIONS ARE SUBJ	HE PROPERTY OF PRATION. NO RIGHTS EIMPLIED. ALL ECT TO NORMAL	B C- AT04-08PA-LE11	VISION 1	
		MANUFACTURING VARI	ATIONS.	SCALE: NONE SHEET 1 OF	2	

		REVISIONS REV ECO DESCRIPTION DATE BY APPR
FOR REFE	RENCE ONLY	4X R1.52±0.12 37.72±0.12 27.20±0.12 4X Ø4.29±0.07
FRONT MOUNT	REAR MOUNT	RECOMMENDED CUTOUT FRONT AND REAR MOUNT
		AT04-08PA-LE11 PART NUMBER DESCRIPTION ITEM
		QUANTITY MATERIALS LIST
		UNLESS OTHERWISE SPECIFIED 1) All dimensions are in metric(mm). 2) Tolerances are as follows: 1 PL DEC 30.30 Produces ± 10 Produces ± 10

AT Series™ - Contact Size 16 Options

Machined Contacts, Sockets & Pins				
Part Number Description		Size	AWG	Туре
AT60-215-1631	Male Contact - Pin, Gold-plated	16	14	Machined
AT62-209-1631	Female Contact - Socket, Gold-plated	16	14	Machined
AT60-215-16141	Male Contact - Pin, Nickel-plated	16	14	Machined
AT62-209-16141	Female Contact - Socket, Nickel-plated	16	14	Machined
AT60-202-1631	Male Contact - Pin, Gold-plated 16 16-20		Machined	
AT62-201-1631	Female Contact - Socket, Gold-plated 16 16-20		16-20	Machined
AT60-202-16141	Male Contact - Pin, Nickel-plated 16 16-20 1		Machined	
AT62-201-16141	Female Contact - Socket, Nickel-plated 16 16-20		16-20	Machined
AT60-202-1631-22	Male Contact - Pin, Gold-plated		22-24	Machined
AT62-201-1631-22	P22 Female Contact - Socket, Gold-plated 16 22-24		Machined	
AT60-202-16141-22	AT60-202-16141-22 Male Contact - Pin, Nickel-plated 16 22-24 Mach		Machined	
AT62-201-16141-22 Female Contact - Socket, Nickel-plated 16 22-24 Machin			Machined	

Tooling - Machined Contacts			
Part	Part Number	Description	
	CA-5D12	Universal Hand Crimp Tool, Size 12/16/20 (Machined contacts only)	
5	CA-5E12	Pneumatic Crimp Tool, Size 12/16/20 (Machined contacts only)	

Contact Removal Tools			
Part	Part Number	Description	
	ATRT-100	Used for removal of contacts for A Series™ products	
	AT11-310-1605	Contact Removal Tool, Plastic, Size 16	
4	A114017	Sealing Plug, Size 16, White	

Stamped & Formed Contacts, Sockets & Pins				
Part Number	Description	Size	AWG	Туре
AT60-14-0144	Male Contact - Pin, Gold-plated	16	14-16	Stamped & Formed
AT62-14-0144	Female Contact - Socket, Gold-plated	16	14-16	Stamped & Formed
AT60-14-0122	Male Contact - Pin, Nickel-plated	16	14-16	Stamped & Formed
AT62-14-0122	Female Contact - Socket, Nickel-plated	16	14-16	Stamped & Formed
AT60-16-0144	Male Contact - Pin, Gold-plated	16	16-18	Stamped & Formed
AT62-16-0144	Female Contact - Socket, Gold-plated	16	16-18	Stamped & Formed
AT60-16-0122	Male Contact - Pin, Nickel-plated	16	16-18	Stamped & Formed
AT62-16-0122	Female Contact - Socket, Nickel-plated	16	16-18	Stamped & Formed
AT60-16-0644	Male Contact - Pin, Gold-plated	16	18-20	Stamped & Formed
AT62-16-0644	Female Contact - Socket, Gold-plated	16	18-20	Stamped & Formed
AT60-16-0622	Male Contact - Pin, Nickel-plated	16	18-20	Stamped & Formed
AT62-16-0622	Female Contact - Socket, Nickel-plated	16	18-20	Stamped & Formed
AT60-16-0844	Male Contact - Pin, Gold-plated	16	20-22	Stamped & Formed
AT62-16-0844	Female Contact - Socket, Gold-plated	16	20-22	Stamped & Formed
AT60-16-0822	Male Contact - Pin, Nickel-plated	16	20-22	Stamped & Formed
AT62-16-0822	Female Contact - Socket, Nickel-plated	16	20-22	Stamped & Formed

Tooling - Stamped & Formed Contacts					
Part	Part Part Number Description				
	MFX-3950	Crimp Die - Size 16, 18-20AWG (S&F contacts only)			
	MFX-3953	Crimp Die - Size 16, 16-18AWG (S&F contacts only)			
	MFX-3975	Crimp Die - Size 16, 14-16AWG (S&F contacts only)			
	MFX-3990	Crimp Die - Size 16, 20-22AWG (S&F contacts only)			
	ATT-16-00	Hand Crimp Tool - Size 16, 14-16AWG (S&F contacts only)			
	ATT-16-01	Hand Crimp Tool - Size 16, 18-20AWG (S&F contacts only)			
	ATT-1612-03	Hand Crimp Tool - Size 16, 20-22AWG (S&F contacts only)			

Amphenol Sine Systems 44724 Morley Drive Clinton Township, MI 48036 USA www.amphenol-sine.com 09/2021