

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

REVISIONS

© COPYRIGHT 20 BY -

ALL RIGHTS RESERVED.

LTR	DESCRIPTION	DATE	DWN	APVD
A	RELEASE	03.MAR.'09	GC	JK
B	REVISED<ECR-14-008909>	21.OCT.'14	SJ	HG

TABLE 1. APPLICABLE REC. CONTACT.

REC.	PART NO.	WIRE RANGE<mm <sup>3</sup> >	INSULATION DIA.<mm> (FLR)
MCP 1.5	1241378	0.2-0.35	1.1-1.4
	1241380	0.5-1.0	1.4-2.1
	1418884	1.5	2.16-2.4

ISD VIEW

TABLE 2. APPLICABLE SINGLE WIRE SEALS

WIRE RANGE<mm <sup>3</sup> >	INSULATION DIA. (mm)	COLOR	PART NO.
0.35-0.50	1.2-1.6	RED	964971-1
0.50-0.75	1.4-1.9	GREY	963530-1
1.00-1.50	1.9-2.4	YELLOW	964972-1
	DEAD END PLUG	WHITE	963531-1

NOTE ;

1. THE COVER OF REC. HSG ASS'Y MUST BE ORDERED SEPARATELY.  
 2. APPLICABLE REC. CONTACT ; SEE TABLE 1.  
 3. APPLICABLE SINGLE WIRE SEAL ; SEE TABLE 2.  
 4. THE MATING TAB HSG ASS'Y P/N : 1897686-2  
 5. GENERAL TOLERANCE :  $\pm 0.3$ ,  $\pm 3.0$  °  
 6. CURCUIT NO.

NO.	PART NO.	DESCRIPTION	MATERIAL	COLOR	Q'TY
4	2005886-1	INNER SEAL	SILICON	ORANGE	1
3	1897691-2	LEVER	PBT-GF20	BLACK	1
2	1897690-2	CAVITY PLUG HSG	PA6-GB20-GF10	BLACK	1
1	1897689-2	REC. HSG	PBT-GF20	BLACK	1

REC. ASS'Y	DESCRIPTION
1897688-2	ASS'Y P/N

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN

SJ CHOI

CHK

KT LIM

APVD

HG CHO

PRODUCT SPEC

APPLICATION SPEC

WEIGHT

CUSTOMER DRAWING

DIMENSIONS:

mm

TOLERANCES UNLESS OTHERWISE SPECIFIED

0 PLC	$\pm 0.5$
1 PLC	$\pm 0.13$
2 PLC	$\pm 0.13$
3 PLC	$\pm 0.013$
4 PLC	$\pm 0.0001$
ANGLES	$\pm$

MATERIAL

FINISH

NAME

-

-

-

-

-

-

-

-

-

-

-

-

TE Connectivity

MCP1.5 SEALED 18P REC. HSG ASS'Y

SIZE

A3

CAGE CODE

00779

DRAWING NO

C-1897688

RESTRICTED TO

-

SCALE 1:1

SHEET 1 OF 1

REV B

1470-19 (3/13)