TOP 1.5 GS/7.62/90
Single-Level
90° Orientation
Without Test Points
Ex'e' Increased Safety







TOP 1.5 GS/7.62/90 BL
Single-Level
90° Orientation
Without Test Points
Ex'e' Increased Safety







TOP 1.5 GS/7.62/180
Single-Level
180° Orientation
Without Test Points
Ex'e' Increased Safety







Technical Data	BVS	UL	BVS
Rated Voltage	250 V	90 V	250 V
Rated Current	16 A	-	16 A
Wire Size	1.5 mm²	1.5 mm²	1.5 mm²
Strip Length	10 mm	10 mm	10 mm
Torque Nm (lb. in.)	0.5 (4.4)	0.5 (4.4)	0.5 (4.4)
Pin Length	3.5 mm	3.5 mm	3.5 mm
Certificate No.	BVS 89 B 7001 U	-	BVS 89 B 7001 U

Poles	Type	Part No.	Poles	Type	Part No.	Poles	Type	Part No.
1**	TOP 1.5 GS/7.62/90/1 OG	**153976**	1***	TOP 1.5 GS/7.62/90/1 BL	**153978**	1**	TOP 1.5 GS/7.62/180/1 OG	**153616**

Notes: Other solder pin lengths are available upon request.
See pages 138-141 for marking materials and other accessories.
***End plate (AP) part no. 56978 is required.*
****End plate (AP) part no. 56976 is required.*