



NOTES: Finish (Plating Thickness in Micro-inches)

1. Brass
2. Nickel Pl. 100 Min. Thick over Copper Pl. 50 Min. Thick
3. Gold Pl. 3 Min Thick over Nickel Pl. 50 Min. Thick over Copper Pl. 50 Min. Thick
4. DELRIN

Crimped Ferrule
Hex Crimp Size .178 (4.5)
Crimped Contact Pin
Hex Crimp Size .068 (1.7)

RoHS Compliant

9	Ferrule	Note 1	Note 2	1	
8	Contact Pin	Note 1	Note 3	1	
7	Washer	Note 1	Note 2	1	
6	Spring	SK5	Note 2	1	
5	Retaining Ring	Note 1	Note 2	1	
4	Gasket	Rubber	Red	1	
3	Insulator	Note 4	Natural	1	
2	Body	Note 1	Note 2	1	
1	Shell	Note 1	Note 2	1	
No.	Description	Material	Finish	Q'ty	Drawing No.

Dimensions are in Inches
Unless Otherwise Specified
Tolerances
0.5-6 = ±0.2
6-30 = ±0.4
30-120 = ±0.6
120-315 = ±1
315-1000 = ±1.6
1000-2000 = ±2.4

Part No.	
Approved	Date 12-14-2010
Checked	Date 12-14-2010
Drawn	Date 12-14-2010

NTE Electronics	
Title	BNC Crimp Plug (For Belden 8218 Cable)
Drawing No.	06-B006
File No.	