

# XY2CD111

Simple rope pull switch, Telemecanique  
Emergency stop rope pull switches XY2C,  
cable 240 VAC 10 A XY2Cd



## Main

Range of Product	Telemecanique Emergency stop rope pull switches XY2C
Product or Component Type	Simple rope pull switch
Device short name	XY2CD
Housing colour	Blue
Overtoltage category	Class I EN/IEC 61140 Class I NF C 20-030

## Complementary

Trigger cable maximum length	19.69 ft (6 m)
Body Material	Zamak
Head material	Plastic
[Us] rated supply voltage	240 V
Contacts type and composition	1 NC + 1 NO
Contact operation	Snap action
Resistance to wrenching	237 DaN operating head 36 daN operating ring
Cable entry number	3 3 entries tapped for Pg 13.5 cable gland Pg 13.5
Mechanical durability	1500000 cycles
[Ie] rated operational current	3 A 240 V, AC-15, A300 EN/IEC 60947-5-1 appendix A 0.27 A 250 V, DC-13, Q300 EN/IEC 60947-5-1 appendix A
[Ithe] conventional enclosed thermal current	10 A
[Ui] rated insulation voltage	400 V 3)EN/IEC 60947-1 300 VUL 508 300 VCSA C22.2 No 14
Compatibility code	XY2CD

## Environment

Product certifications	CCC CE
Ambient air temperature for operation	-4...158 °F (-20...70 °C)
IP degree of protection	IP66 IEC 60529

## Ordering and shipping details

Category	22441 - LIMIT SWITCHES,CABLE PULL
Discount Schedule	T
GTIN	3389110662016
Nbr. of units in pkg.	1
Package weight(Lbs)	9.91 oz (281 g)
Returnability	No
Country of origin	FR

## Packing Units

Unit Type of Package 1	PCE
Package 1 Height	1.26 in (3.2 cm)
Package 1 width	2.56 in (6.5 cm)
Package 1 Length	5.75 in (14.6 cm)
Unit Type of Package 2	S01
Number of Units in Package 2	16
Package 2 Weight	10.46 lb(US) (4.745 kg)
Package 2 Height	5.91 in (15 cm)
Package 2 width	5.91 in (15 cm)
Package 2 Length	15.75 in (40 cm)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

## Contractual warranty

Warranty	18 months
----------	-----------