

## Accessories

### SIHA 3/G20

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

### Product image



### DCS marshalling

Our innovative PRV terminal blocks for DCS marshalling featuring a PUSH IN connection and our multifunctional DCS marshalling terminals featuring a screw connection (WMF) not only save space in the panel; they also guarantee more effective signal transmission in process control systems.

### General ordering data

|            |  |
|------------|--|
| Type       | SIHA 3/G20   |
| Order No.  | <a href="#">7921560000</a>   |
| Version    | Accessories, Fuse holder, Rated cross-section: Plug-in connection, Wemid, Dark Beige, Operating instructions/catalogue |
| GTIN (EAN) | 4032248264643  |
| Qty.       | 25 pc(s).  |

## Data sheet

### Accessories SIHA 3/G20

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

## Technical data

### Dimensions and weights

|            |          |                 |            |
|------------|----------|-----------------|------------|
| Width      | 6 mm     | Width (inches)  | 0.236 inch |
| Height     | 39.38 mm | Height (inches) | 1.55 inch  |
| Depth      | 63.1 mm  | Depth (inches)  | 2.484 inch |
| Net weight | 6.44 g   |                 |            |

### Temperatures

|                                   |        |                                  |                     |
|-----------------------------------|--------|----------------------------------|---------------------|
| Operating temperature range, max. | 120 °C | Operating temperature, max.      | 120 °C              |
| Operating temperature, min.       | -50 °C | Operating temperature            | -50 °C.../TX]120 °C |
| Continuous operating temp., min.  | -50 °C | Continuous operating temp., max. | 120 °C              |

### Material data

|          |       |                           |       |
|----------|-------|---------------------------|-------|
| Material | Wemid | Insulating material       | Wemid |
| Colour   | Beige | UL 94 flammability rating | V-0   |

### System specifications

|         |                |                          |    |
|---------|----------------|--------------------------|----|
| Version | Fuse cartridge | End cover plate required | No |
|---------|----------------|--------------------------|----|

### Additional technical data

|                     |                                      |                  |         |
|---------------------|--------------------------------------|------------------|---------|
| Installation advice | Operating instructions/<br>catalogue | Type of mounting | Plugged |
|---------------------|--------------------------------------|------------------|---------|

### Conductors for clamping (rated connection)

|                    |                    |
|--------------------|--------------------|
| Type of connection | Plug-in connection |
|--------------------|--------------------|

### Rating data

|                                 |       |                    |       |
|---------------------------------|-------|--------------------|-------|
| Rated voltage                   | 250 V | Rated current      | 6.3 A |
| Rated impulse withstand voltage | 4 kV  | Pollution severity | 3     |

### Classifications

|            |             |            |             |
|------------|-------------|------------|-------------|
| ETIM 3.0   | EC000036    | ETIM 4.0   | EC000036    |
| ETIM 5.0   | EC000036    | ETIM 6.0   | EC002848    |
| UNSPSC     | 30-21-18-11 | eClass 5.1 | 27-14-11-16 |
| eClass 6.2 | 27-14-92-14 | eClass 7.1 | 27-14-92-14 |
| eClass 8.1 | 27-14-11-49 | eClass 9.0 | 27-14-11-49 |
| eClass 9.1 | 27-14-11-92 |            |             |

### Approvals

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

### Downloads

|                    |  |
|--------------------|--|
| Brochure/Catalogue | <a href="#">CAT 1 TERM 16/17 EN</a>      |
| Engineering Data   | <a href="#">EPLAN, WSCAD, Zuken E3.S</a> |
| Engineering Data   | <a href="#">STEP</a>                     |
| User Documentation | <a href="#">Beipackzettel_SIHA3.pdf</a>  |