


THIS IS A CONTROLLED DOCUMENT.



- NOTES:
- ▲ FOR FIELD REPLACEMENT ONLY.
 - ▲ USED IN PLACE OF ITEM 38 WHEN INSULATION CRIMP IS NOT USED.
 - 3- ONLY THE PARTS & HARDWARE LISTED ON PARTS LIST ARE USED ON THIS APPLICATOR.
- KEY:
- RECOMMENDED SPARES.
 - ▼ LUBRICATE DAILY, USING NO. 20 MACHINE OIL.
 - GREASE LIGHTLY.

REQ.	PART NO.	DESCRIPTION	NO.	REQ.	PART NO.	DESCRIPTION	NO.
			162	1	690517-1	SPACER	71
			161	1	22594-8	NUT, HEX	70
			160	1	240628-1	PLATE, ADJUSTMENT	69
			159	1	240626-1	SHAFT, PIVOT	68
			158	1	240633-1	BUSHING	67
			157	1	240630-1	LEVER, INTERMEDIATE	66
			156	1	240629-1	BLOCK, PIVOT	65
2	21045-3	RING, RETAINING "C" .187 DIA.	155	1	240632-1	SCREW, ADJ.	64
			154	1	240659-1	PIN, CAM ROLLER	63
			153	1	240658-1	ROLLER, CAM	62
1	21055-5	WASHER, FLAT (#8) LIFTER SPRING	152	1	690649-1	ROD, FEED	61
2	21055-7	WASHER, FLAT (#10) GUARD	151	1	690648-1	PLATE, WEAR	60
1	5-21004-7	SCREW SKT. HD. SHLDR (.250 DIA X .25) DRAG ARM	150	1	240621-1	CAP, RAM	59
1	21004-2	SCREW SKT. HD. SHLDR (.250 DIA X .50) DRAG	149	1	690553-1	HOUSING	58
			148				57
1	1-21030-1	PIN, DOWEL (.187 DIA X .50) LEVER	147	1	690529-1	ARM, FEED	56
1	1-21030-7	PIN, DOWEL (.187 DIA X 1.50) HOUSING	146	1	240624-1	PIN, FEED FINGER	55
2	21030-2	PIN, DOWEL (.250 DIA X .75) BASE PLATE	145	1	691499-1	SPRING, FEED FINGER	54
			144	1	690532-1	FINGER, FEED	53
2	5-21028-1	PIN, SLOTTED SPRING (.12 DIA X .50) FEED ADJ ROD	143	1	240634-1	LEVER, TERMINAL	52
REF.	21028-2	PIN, SLOTTED SPRING (.06 DIA X .25) RAM	142				51
9	21028-0	PIN, SLOTTED SPRING (.12 DIA X .25) CAM	141				50
2	21024-3	WASHER, LOCK (#6) REAR STRIP GUIDE	140	1	7-21002-9	BOLT, CRIMPER	49
2	21024-4	WASHER, LOCK (#8) SHEAR BLADE	139	1	238015-1	CAM POST-FEED 1 5/8 STROKE	48
			138	1	22353-8	SCREW SHOULDER (.187 DIA X .250)	47
1	21024-4	WASHER, LOCK (#8) FEED FINGER	137	1	690402-1	BLOCK, INSULATION ADJUSTMENT	46
2	21024-4	WASHER, LOCK (#8) FRONT STRIP GUIDE	136	1	690191-1	PLUG, NYLON	45
2	21024-4	WASHER, LOCK (#8) STRIPPER	135	1	690550-1	RAM	44
			134	1	690125-1	WASHER, LAMINATED	43
2	21024-5	WASHER, LOCK (#10) SHEAR PLATE	133	1	690124-1	WASHER, RAM	42
2	21024-5	WASHER, LOCK (#10) FEED ADJ. PLATE	132			SPACER, DISC.	41
4	21024-5	WASHER, LOCK (#10) HOUSING CAP	131	2	23241-6	BALL, STEEL	40
1	21002-3	SCREW BTN. HD. SKT. CAP (4-40 X .12) TERMINAL LIFT	130	2	690170-1	SPRING, COMPRESSION	39
1	21003-9	SCREW FLAT HD. SKT. CAP (6-32 X .38) CAM	129	1	690142-1	DISC, INSULATION	38
1	21068-5	NUT, HEX MACHINE (6-32) FEED ADJ.	128	1	3-690141-8	DISC, WIRE	37
1	21018-7	NUT, HEX MACHINE (10-32) DRAG SPRING	127	1	22480-5	WASHER, SPRING	36
			126	1	690212-1	POST, RAM	35
1	21009-2	SCREW SKT. SET (NYLOK) (1/4-20 X .25) C.P. RAM	125	1	690610-3	SPACER, STRIP GUIDE	34
2	21006-7	SCREW SKT. SET (6-32 X .12) C.P. DISC.	124	1	690551-1	PLATE SHEAR, SIDE	33
1	21002-0	SCREW BTN. HD. SKT. CAP (8-32 X .25) SHEAR BLOCK	123	1	690549-5	BLADE, SHEAR, SIDE	32
1	21002-1	SCREW, BTN. HD. SOC. CAP (8-32 X .38) SHEAR BLOCK	122				31
2	21002-2	SCREW BTN. HD. SKT. CAP (8-32 X .50) TERM. LIFTER	121		690453-1	ANCHOR, SPACER	30
1	22733-8	SCREW, BTN. HD. SOC. CAP (NYLOK) (8-32 X .38) ANVIL	120				29
3	3-21000-4	SCREW SKT. HD. CAP (10-32 X .38) S.G. PLATE	119				28
4	3-21002-3	SCREW BTN. HD. SKT. CAP (1/4-20 X .50) BASE PLATE	118	1	690634-1	STRIPPER	27
2	3-21002-5	SCREW BTN. HD. SKT. CAP (1/4-20 X .75) HOUSING	117	1	690554-1	PLATE, BASE	26
2	2-21000-0	SCREW, SKT. HD. CAP (6-32 X .50) REAR STRIP GUIDE	116	1	690555-1	BLOCK, BASE	25
2	2-21002-1	SCREW, BTN. HD. CAP (8-32 X .3) REAR SHEAR BLADE	115	1	690528-1	PLATE, STRIP GUIDE	24
2	2-21000-5	SCREW SKT. HD. CAP (8-32 X .25) CHIP GUARD	114	1	469487-1	GUARD, CHIP	23
1	21000-5	SCREW SKT. HD. CAP (8-32 X .25) FEED FINGER	113	1	7-22282-5	SPRING, DRAG	22
2	21000-8	SCREW SKT. HD. CAP (8-32 X .62) STRIPPER	112	1	240636-1	LEVER, DRAG	21
1	1-21000-8	SCREW SKT. SOC. HD. CAP (6-32 X .25) STRIP GUIDE SPA	111	1	240676-2	DRAG, STOCK	20
1	2-21002-3	SCREW BTN. HD. CAP (8-32 X .62) FRONT STRIP GUIDE	110	1	690530-2	GUIDE, STRIP, REAR	19
1	2-21002-4	SCREW BTN. HD. CAP (8-32 X .75) FRONT STRIP GUIDE	109	1	690531-2	GUIDE, STRIP, FRONT	18
1	3-21000-4	SCREW SKT. HD. CAP (10-32 X .38) PIVOT BLOCK	108	1	238008-1	SPRING, ANCHOR	17
1	3-21000-7	SCREW SKT. HD. CAP (10-32 X .75) SHEAR PLATE	107	3	22288-0	SPRING, FEED RETURN	16
1	3-21000-7	SCREW SKT. HD. CAP (10-32 X .75) SHEAR PLATE	106				15
1	3-21000-9	SCREW SKT. HD. CAP (10-32 X 1.00) DRAG SPRING	105		690645-1	SPRING, TERM. LIFTER	14
2	3-21000-6	SCREW SKT. HD. CAP (10-32 X .62) FEED ADJ. PLATE	104		690644-1	BUSHING, TERM. LIFTER	13
1	4-21000-1	SCREW SKT. HD. CAP (10-32 X 1.50) CAP	103		690636-1	LIFTER, TERMINAL	12
3	4-21000-0	SCREW SKT. HD. CAP (10-32 X 1.25) CAP	102	1	690631-1	PLATE, REAR SHEAR	11
2	3-21000-5	SCREW SKT. HD. CAP (10-32 X .50) CAM	101	1	469488-1	SPACER, SHEAR PLATE	10
REF.	455750-5	GUARD ASSY	80	1	690552-2	PLATE, FRONT SHEAR	9
	465184-9	LUBRICATOR ASSY.	79	1	1240694-1	ANVIL	8
	22014-1	OIL, SYNTHETIC	78	1	690612-1	BLADE, SHEAR	7
	454406-1	SPACER, LUBRICATOR BRACKET	77				6
			76				5
			75	1	238009-1	SPACER, TUBULAR, INS. CRIMPER	4
2	21017-2	SCR. DRIVE (#2 X .19) ID PLATE	74	1	690406-3	CRIMPER, INSULATION	3
1	461264-1	PLATE, ID	73			SPACER, INSULATION CRIMPER	2
2	690603-1	SPRING, ASSIST	72	1	453338-8	CRIMPER, WIRE	1

TERM APPL SPEC 114-2079

CRIMPING DATA				THIS APPLICATOR WILL APPLY
PAD LETTER	CRIMP HEIGHT	WIRE SIZE	WIRE STRIP LENGTH	62418
A	.067	16		
B	.060	18		
C	.056	20		
D	.049	22		
CRIMP SIZE	TYPE	FEED		
WIRE	.090 F			
INSULATION	.155 F	.560		
INSULATION RANGE	WIRE RANGE	APPLICATOR INSTRUCTION	AI 6090	
.090-.140	22-16			
REMARKS: POST-FEED AMPOMATOR				
SET UP PAGE	LAYOUT NO.	AMP HARRISBURG, PENNA.		
679108-1	865			
DRAWN	APPROVED	REV. E		
11-13-75	11/14/75			
E REV PER ECN		R 12550 10/14/78		
D REV PER ECN		R 1784 10/14/78		
C REV PER ECN		R 1714 10/14/77		
B REV PER ECN		R 1627 10/14/76		
A REV PER ECN				
LTR	REVISION RECORD	ECN	DATE	LTR

MINIATURE QUICK CHANGE APPLICATOR
FLAG FASTON E.F. (COMM. FLAG)

CUSTOMER AND ASSEMBLY DRAWING

1-625994