



# DTV1500SD

## (CRT TV HORIZONTAL DEFLECTION) HIGH VOLTAGE DAMPER DIODE

**Table 1: Main Product Characteristics**

$I_{F(AV)}$	6 A
$I_{Fpeak (max)}$	12 A
$V_{RRM}$	1500 V
$T_j$	175°C
$V_F (typ)$	1.1 V
$t_{rr} (typ)$	150 ns
$V_{FP} (typ)$	26 V

### FEATURES AND BENEFITS

- High breakdown voltage capability
- Specified turn on switching characteristics
- Very fast recovery diode
- Low static and peak forward voltage drop for low dissipation
- Insulated package (TO-220FPAC):  
Insulating voltage = 2000V DC  
Capacitance = 12 pF
- Planar technology allowing high quality and best electrical characteristics


### DESCRIPTION

High voltage diode especially designed for horizontal deflection stage in standard and high resolution displays for TVs.

This device is packaged in TO-220FPAC (insulated package).

**Table 3: Absolute Maximum Ratings**

Symbol	Parameter	Value	Unit
$V_{RRM}$	Repetitive peak reverse voltage	1500	V
$I_{F(RMS)}$	RMS forward voltage	15	A
$I_{Fpeak}$	Peak working forward current	$F = 56kHz$ 12	A
$I_{FSM}$	Surge non repetitive forward current	$t_p = 10ms$ sinusoidal 50	A
$T_{stg}$	Storage temperature range	-65 to 175	°C
$T_j$	Maximum operating junction temperature	175	°C



**Table 2: Order Code**

Part Number	Marking
DTV1500SDFP	DTV1500SDFP

**Table 4: Thermal Resistance**

Symbol	Parameter	Value (max).	Unit
$R_{th(j-c)}$	Junction to case thermal resistance	5.8	°C/W

**Table 5: Static Electrical Characteristics**

Symbol	Parameter	Test conditions		Typ	Max.	Unit
$I_R$ *	Reverse leakage current	$T_j = 25^\circ\text{C}$	$V_R = V_{RRM}$		100	$\mu\text{A}$
		$T_j = 125^\circ\text{C}$		100	1000	
$V_F$ **	Forward voltage drop	$T_j = 25^\circ\text{C}$	$I_F = 6\text{A}$	1.2	1.75	V
		$T_j = 125^\circ\text{C}$		1.1	1.5	

Pulse test: \*  $t_p = 5\text{ ms}$ ,  $\delta < 2\%$

\*\*  $t_p = 380\ \mu\text{s}$ ,  $\delta < 2\%$

To evaluate the conduction losses use the following equation:  $P = 1.23 \times I_{F(AV)} + 0.045 I_F^2(\text{RMS})$


**Table 6: Recovery Characteristics**

Symbol	Parameter	Test conditions		Typ	Max.	Unit
$t_{rr}$	Reverse recovery time	$T_j = 25^\circ\text{C}$	$I_F = 1\text{A}$ $di_F/dt = -50\text{ A}/\mu\text{s}$ $V_R = 30\text{V}$	150	250	ns
			$I_F = 100\text{mA}$ $I_{rr} = 10\text{mA}$ $I_R = 100\text{mA}$	1000		


**Table 7: Turn-On Switching Characteristics**

Symbol	Parameter	Test conditions		Typ	Max.	Unit
$t_{fr}$	Forward recovery time	$T_j = 100^\circ\text{C}$	$I_F = 6\text{A}$ $di_F/dt = 80\text{ A}/\mu\text{s}$ $V_{FR} = 3\text{V}$		500	ns
$V_{FP}$	Peak forward voltage	$T_j = 100^\circ\text{C}$	$I_F = 6\text{A}$ $di_F/dt = 80\text{ A}/\mu\text{s}$	26	36	V


**Figure 1: Conduction losses versus average current ( $\delta=0.45$ )**




**Figure 2: Forward voltage drop versus forward current**




**Figure 3: Reverse recovery charges versus  $dI_F/dt$  (typical values)**




**Figure 4: Peak reverse recovery current versus  $dI_F/dt$  (typical values)**




**Figure 5: Transient peak forward voltage versus  $dI_F/dt$  (typical values)**




**Figure 6: Forward recovery time versus  $dI_F/dt$  (typical values)**




**Figure 7: Relative variations of dynamic parameters versus junction temperature**



**Figure 8: Junction capacitance versus reverse voltage applied (typical values)**



**Figure 9: Relative variation of thermal impedance junction case versus pulse duration**



Obsolete Product(s)

Figure 10: TO-220FPAC Package Mechanical Data

REF.	DIMENSIONS			
	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A	4.4	4.6	0.173	0.181
B	2.5	2.7	0.098	0.106
D	2.5	2.75	0.098	0.108
E	0.45	0.70	0.017	0.027
F	0.75	1	0.030	0.039
F1	1.15	1.70	0.045	0.067
F2	1.15	1.70	0.045	0.067
G	4.95	5.20	0.195	0.204
G1	2.40	2.70	0.094	0.106
H	10	10.4	0.393	0.409
L2	16 Typ.		0.63 Typ.	
L3	28.6	30.6	1.126	1.204
L4	9.8	10.6	0.385	0.417
L6	15.9	16.4	0.626	0.645
L7	9.00	9.30	0.354	0.366
Di.	3	3.20	0.118	0.126

Table 8: Ordering Information

Part Number	Marking	Package	Weight	Base qty	Delivery mode
DTV1500SDFP	DTV1500SDFP	TO-220FPAC	1.8 g	50	Tube

Table 9: Revision History

Date	Revision	Description of Changes
05-Jul-2004	1	First issue.
25-Nov-2004	2	Table 3 page 1: $T_{stg}$ and $T_j$ from upgraded from 150°C to 175°C.
16-Mar-2005	3	$I_{Fpeak}$ parameter included.

Information furnished is believed to be accurate and reliable. However, STMicroelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of STMicroelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. STMicroelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of STMicroelectronics.

The ST logo is a registered trademark of STMicroelectronics.  
All other names are the property of their respective owners

© 2005 STMicroelectronics - All rights reserved

**STMicroelectronics group of companies**

Australia - Belgium - Brazil - Canada - China - Czech Republic - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan - Malaysia - Malta - Morocco - Singapore - Spain - Sweden - Switzerland - United Kingdom - United States of America

**[www.st.com](http://www.st.com)**