


Gallium Nitride 28V, 200W RF Power Transistor

Built using the SIGANTIC® NRF1 process - A proprietary GaN-on-Silicon technology

FEATURES

- Optimized for narrowband and broadband applications from DC – 1200MHz
- 200W P_{3dB} CW power at 900MHz in quadrature combined or push-pull configuration
- 90W CW power from 500-1000MHz in application design [AD-014](#)
- High efficiency from 14V to 28V
- 1.0 °C/W R_{TH} with maximum T_J rating of 200°C
- Robust up to 10:1 VSWR mismatch at all angles with no device degradation
- Subject to EAR99 export control



DC – 1200 MHz
14 – 28 Volt
GaN HEMT



RF Specifications (CW): V_{DS} = 28V, I_{DQ} = 1400mA¹, Frequency = 900MHz, T_A = 25°C, Measured in Nitronex Quadrature Combined Test Fixture².

Symbol	Parameter	Min	Typ	Max	Units
P _{3dB}	Average Output Power at 3dB Gain Compression	52.0	53.0	-	dBm
G _{SS}	Small Signal Gain	17.3	18.3	-	dB
η	Drain Efficiency at 3dB Gain Compression ²	57	63	-	%
VSWR	10:1 VSWR at all phase angles	No change in device performance			

Note 1: 700mA per transistor. Each gate should be biased independently to set desired I_{DQ}.

Note 2: Includes ~ 0.2 dB quadrature combiner loss.

Typical 2-Tone Performance: V_{DS} = 28V, I_{DQ} = 1400mA¹, Frequency = 900MHz, Tone spacing = 1MHz, T_A = 25°C Measured in Nitronex Quadrature Combined Test Fixture².

Symbol	Parameter	Typ	Units
P _{3dB,PEP}	Peak Envelope Power at 3dB Gain Compression	53.4	dBm
P _{1dB,PEP}	Peak Envelope Power at 1dB Gain Compression	52.6	dBm
P _{IMD3}	Peak Envelope Power at -35dBc IMD3	50.8	dBm

Note 1: 700mA per transistor. Each gate should be biased independently to set desired I_{DQ}.

Note 2: Includes ~ 0.2 dB quadrature combiner loss.

DC Specifications: Per Transistor, $T_A = 25^\circ\text{C}$

Symbol	Parameter	Min	Typ	Max	Units
Off Characteristics					
V_{BDS}	Drain-Source Breakdown Voltage ($V_{GS} = -8\text{V}$, $I_D = 36\text{mA}$)	100	-	-	V
I_{DLK}	Drain-Source Leakage Current ($V_{GS} = -8\text{V}$, $V_{DS} = 60\text{V}$)	-	9	18	mA
On Characteristics					
V_T	Gate Threshold Voltage ($V_{DS} = 28\text{V}$, $I_D = 36\text{mA}$)	-2.3	-1.8	-1.3	V
V_{GSQ}	Gate Quiescent Voltage ($V_{DS} = 28\text{V}$, $I_D = 700\text{mA}$)	-2.0	-1.5	-1.0	V
R_{ON}	On Resistance ($V_{GS} = 2\text{V}$, $I_D = 270\text{mA}$)	-	0.13	0.14	Ω
$I_{D,MAX}$	Drain Current ($V_{DS} = 7\text{V}$ pulsed, 300 μs pulse width, 0.2% duty cycle)	19.0	20.5	-	A

Absolute Maximum Ratings: Not Simultaneous, Per Transistor, $T_A = 25^\circ\text{C}$ Unless Otherwise Noted

Symbol	Parameter	Max	Units
V_{DS}	Drain-Source Voltage	100	V
V_{GS}	Gate-Source Voltage	-10 to 3	V
I_G	Gate Current	180	mA
P_T	Total Device Power Dissipation (Derated above 25°C), both transistors on	175	W
θ_{JC}	Thermal Resistance (Junction-to-Case), composite for both transistors on, $T_J = 180^\circ\text{C}$	1.0	$^\circ\text{C}/\text{W}$
	Thermal Resistance (Junction-to-Case), one transistor on, one off, $T_J = 180^\circ\text{C}$	1.8	
T_{STG}	Storage Temperature Range	-65 to 150	$^\circ\text{C}$
T_J	Operating Junction Temperature	200	$^\circ\text{C}$
HBM	Human Body Model ESD Rating (per JESD22-A114)	1C (>1000V)	
MM	Machine Model ESD Rating (per JESD22-A115)	A (>100V)	
CDM	Charge Device Model ESD Rating (per JESD22-C101)	IV (>4000V)	

Load-Pull Data, Reference Plane at Device Leads

$V_{DS}=28V$, $I_{DQ}=700mA$, One Single-Ended Transistor, $T_A=25^\circ C$ Unless Otherwise Noted

Table 1: Optimum Source and Load Impedances for CW Gain, Drain Efficiency, and Output Power Performance

Frequency (MHz)	$Z_S (\Omega)$	$Z_L (\Omega)$	P_{SAT} (dBm)	G_{SS} (dB)	Drain Efficiency @ P_{SAT} (%)
500	$1.4 + j0.1$	$2.0 + j0.5$	50.0	24.0	70%
900	$1.6 - j1.5$	$2.3 - j1.5$	50.0	18.5	74%
1200	$1.8 - j2.7$	$3.5 - j2.8$	49.5	16.5	62%





Figure 1 - Optimum Impedances for CW Performance




Figure 2 - Load-Pull Contours, 500MHz, $P_{IN} = 25dBm$, $Z_S = 1.4 + j0.1 \Omega$




Figure 3 - Load-Pull Contours, 900MHz, $P_{IN} = 30dBm$, $Z_S = 1.6 - j1.5 \Omega$




Figure 4 - Load-Pull Contours, 1200MHz, $P_{IN} = 32dBm$, $Z_S = 1.8 - j2.7 \Omega$

Load-Pull Data per Device Lead, Reference Plane at Device Leads

$V_{DS}=28V$, $I_{DQ}=700mA$, One Single-Ended Transistor, $T_A=25^{\circ}C$ unless otherwise noted.




Figure 5 - Typical CW Performance, over Frequency




Figure 6 - Typical CW Performance over Frequency




Figure 7 - Typical Pulsed Performance, Frequency = 900MHz, Duty Cycle = 10%




Figure 8 - Typical CW Performance at $V_{DS} = 20V$, Frequency = 900MHz

Nitronex Quadrature Combined Test Fixture

$V_{DS}=28V$, $I_{DQ}=1400mA$, $T_A=25^{\circ}C$ unless otherwise noted.




Figure 9 - Typical IMD3 Performance, Frequency = 900MHz, Tone spacing = 1MHz




Figure 10 - Typical CW Performance over Temperature, Frequency = 900MHz

Typical Device Characteristics

$V_{DS}=28V$, $I_{DQ}=700mA$, One Single-Ended Transistor, $T_A=25^{\circ}C$ unless otherwise noted.




Figure 11 - Quiescent Gate Voltage (V_{GSQ}) Required to Reach I_{DQ} over Temperature




Figure 12 - MTTF of NRF1 devices as a function of junction temperature

Ordering Information¹

Part Number	Description
NPT1007B	NPT1007 in AC780B-4 Metal-Ceramic Bolt-Down Package

1: To find a Nitronex contact in your area, visit our website at <http://www.nitronex.com>




Figure 13 - AC780B-4 Metal-Ceramic Package Dimensions and Pinout (all dimensions are in inches [mm])

Nitronex, LLC

2305 Presidential Drive
Durham, NC 27703 USA
+1.919.807.9100 (telephone)
+1.919.807.9200 (fax)
info@nitronex.com
www.nitronex.com

Additional Information

This part is lead-free and is compliant with the RoHS directive (Restrictions on the Use of Certain Hazardous Substances in Electrical and Electronic Equipment).

Important Notice

Nitronex, LLC reserves the right to make corrections, modifications, enhancements, improvements and other changes to its products and services at any time and to discontinue any product or service without notice. Customers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All products are sold subject to Nitronex terms and conditions of sale supplied at the time of order acknowledgment. The latest information from Nitronex can be found either by calling Nitronex at 1-919-807-9100 or visiting our website at www.nitronex.com.

Nitronex warrants performance of its packaged semiconductor or die to the specifications applicable at the time of sale in accordance with Nitronex standard warranty. Testing and other quality control techniques are used to the extent Nitronex deems necessary to support the warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

Nitronex assumes no liability for applications assistance or customer product design. Customers are responsible for their product and applications using Nitronex semiconductor products or services. To minimize the risks associated with customer products and applications, customers should provide adequate design and operating safeguards.

Nitronex does not warrant or represent that any license, either express or implied, is granted under any Nitronex patent right, copyright, mask work right, or other Nitronex intellectual property right relating to any combination, machine or process in which Nitronex products or services are used.

Reproduction of information in Nitronex data sheets is permitted if and only if said reproduction does not alter any of the information and is accompanied by all associated warranties, conditions, limitations and notices. Any alteration of the contained information invalidates all warranties and Nitronex is not responsible or liable for any such statements.

Nitronex products are not intended or authorized for use in life support systems, including but not limited to surgical implants into the body or any other application intended to support or sustain life. Should Buyer purchase or use Nitronex, LLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold Nitronex, LLC, its officers, employees, subsidiaries, affiliates, distributors, and its successors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, notwithstanding if such claim alleges that Nitronex was negligent regarding the design or manufacture of said products.

Nitronex and the Nitronex logo are registered trademarks of Nitronex, LLC.
All other product or service names are the property of their respective owners.
©Nitronex, LLC 2012. All rights reserved.