TE Internal #: 1-338086-3

RJ25 Connectors, Single Port, 1 x 1, Standard Profile, RJ Type Jacks

& Plugs, Standard Connector Contact Density, Jack, Standard -

Latch Down

View on TE.com >




Connectors > Modular Jacks & Plugs > RJ25 Connectors











Port Configuration: Single Port Port Matrix Configuration: 1 x 1 Connector Profile: Standard

Modular Jacks & Plugs Products: RJ Type Jacks & Plugs

Connector Contact Density: Standard

Features

Product Type Features

| Grounding Options | None |
|-----------------------------------|-----------------------|
| Connector Product Type | Connector Assembly |
| Modular Jacks & Plugs Products | RJ Type Jacks & Plugs |
| Modular Connector Style | Jack |
| Connector System | Cable-to-Board |
| Connector & Contact Terminates To | Printed Circuit Board |

Configuration Features

| Port Configuration | Single Port |
|----------------------------|-------------|
| Port Matrix Configuration | 1 x 1 |
| Connector Contact Density | Standard |
| PCB Mount Orientation | Vertical |
| Number of Positions | 6 |
| Number of Loaded Positions | 6 |

Body Features



| Connector Profile | Standard |
|--------------------------------------------------------------------|---------------------------|
| Modular Jack Latch Orientation | Standard - Latch Down |
| Contact Features | |
| | Nickel |
| Contact Underplating Material Contact Base Material | Phosphor Bronze |
| Contact Base Material Contact Mating Area Plating Material | Nickel |
| Contact Mating Area Flating Material Contact Current Rating (Max) | 1.5 A |
| PCB Contact Termination Area Plating Material | Tin |
| Termination Features | |
| Termination Method to Printed Circuit Board | Curfoco Mount |
| | Surface Mount |
| Mechanical Attachment | |
| Mating Alignment | Without |
| Connector Mounting Type | Board Mount |
| Panel Mount Feature | With |
| Housing Features | |
| Mating Entry Location | Тор |
| Housing Color | Black |
| Housing Material | G.F. PA 9T |
| Centerline (Pitch) | 1.27 mm[.05 in] |
| Dimensions | |
| Connector Height | 12.7 mm[.5 in] |
| PCB Thickness (Recommended) | 1.57 mm[.062 in] |
| Usage Conditions | |
| Operating Temperature Range | -40 – 70 °C[-40 – 158 °F] |
| Operation/Application | |
| Shielded | No |
| Circuit Application | Signal |
| Industry Standards | |
| Performance Category | Cat 3 |
| UL Flammability Rating | UL 94V-0 |
| Packaging Features | |
| | |



| Packaging Reel Diameter | 36 cm |
|-------------------------------|-------------------------------------------------------------|
| Packaging Method | Piece/Reel, Tape Mounted on Reel |
| Packaging Quantity | 300 |
| Other | |
| Modular Jacks & Plugs Comment | Surface can be used for application by Type II SMD Machine. |

Product Compliance

For compliance documentation, visit the product page on TE.com>

| EU RoHS Directive 2011/65/EU | Compliant |
|-----------------------------------------------|--------------------------------------------------------------------------------------------------------------------------|
| EU ELV Directive 2000/53/EC | Compliant |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold |
| EU REACH Regulation (EC) No. 1907/2006 | Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2023 (233) Does not contain REACH SVHC |
| Halogen Content | Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free |
| Solder Process Capability | Reflow solder capable to 260°C |

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts





Customers Also Bought



TE Part #177905-1
POWER DBL LOCK PLUG HSG 12P



TE Part #177920-1 POWER DBL LOCK PLATE 3.96MM 4POS



TE Part #171826-6 POST HEADER ASSY HORIZ EI





TE Part #171826-7 H-TYPE E.I.S.CONN. 7P ASSY



TE Part #5557785-1 MJ,8POS,R/A,LPF



TE Part #6-390113-1 SKT,SODIMM,144P,SDRAM3.3V,STD, T&R



TE Part #2271597-8

AMPMODU, REC HDR, DR, 2.0PITCH, SMT, 8P



AMPMODU, REC, 2.54, DR, SMT, 9.90 H, 6POS



Documents

Product Drawings 6/6 INV.MOD JACK

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1-338086-3_Z.2d_dxf.zip

RJ25 Connectors, Single Port, 1 x 1, Standard Profile, RJ Type Jacks & Plugs, Standard Connector Contact Density, Jack, Standard - Latch Down



English

Customer View Model

ENG_CVM_CVM_1-338086-3_Z.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1-338086-3_Z.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

82066 - Modular Jacks and MRJ21 Product catalog - Single Port Modular Jacks section

English

Product Specifications

AMP surface mount modular jack

English

Application Specification

English

Product Environmental Compliance

Product Compliance Document

English

Product Compliance Document

English

Agency Approvals

UL Report

English