

# Product data sheet

Specifications



## Netshelter RX 42U Enclosure 600mm x 800mm

NSYSFRSEDC20680

### Overview

**Presentation** NEMA 12 rated assembled enclosure for OT, IT and networking applications. Form factor to easily roll through doorways. Configurable to work as a ventilated enclosure with the addition of Climasys ventilation components. Includes: Front and rear solid doors with handle and insert key, side panels, 19" uprights, bottom plinth, grounding and gland plate at the bottom panel. Ventilation system not included. Can be shipped pre-integrated with UPS, PDU, monitoring components and internal equipment up to 350 lbs.

**Lead time** Usually Ships within 4 Weeks

### Physical

**Height** 2100 mm

**Width** 600 mm

**Depth** 800 mm

**Number of rack unit** 42U

**Product weight** 146 kg

**Mounting mode** Rack-mounted

**Mounting preference** No preference

**Maximum mounting depth** 652 mm

**Max CTO ship weight** 171 kg

**Permanent permissible load** 113 kg dynamic  
400 kg static

### Packing Units

**Unit Type of Package 1** PCE

**Number of Units in Package 1** 1

**Package 1 Height** 228.0 cm

**Package 1 Width** 74.0 cm

**Package 1 Length** 116.0 cm

**Package 1 Weight** 197.0 kg

### Offer Sustainability

**EU RoHS Directive** Not applicable, out of EU RoHS legal scope

### Recommended replacement(s)