

## Circular Connector w. Harax M12 L 5 F



Image is for illustration purposes only. Please refer to product description.

|                    |   |
|--------------------|---|
| Part number        | 21 03 272 2505  |
| Specification      | Circular Connector w. Harax M12 L 5 F   |
| HARTING eCatalogue | <a href="https://b2b.harting.com/21032722505">https://b2b.harting.com/21032722505</a> |

### Identification

|                |                         |
|----------------|-------------------------|
| Category       | Connectors              |
| Series         | Circular connectors M12 |
| Identification | M12-L                   |
| Element        | Cable connector         |
| Specification  | Straight                |

### Version

|                    |  |
|--------------------|--|
| Termination method | HARAX <sup>®</sup> connection technology |
| Gender             | Female                                   |
| Shielding          | Unshielded                               |
| Number of contacts | 5  |
| Coding             | A-coding                                 |
| Locking type       | Screw locking                            |

### Technical characteristics

|                         |                              |
|-------------------------|------------------------------|
| Conductor cross-section | 0.34 ... 0.5 mm <sup>2</sup> |
| Conductor cross-section | AWG 22 ... AWG 20            |
| Wire outer diameter     | ≤2 mm                        |
| Rated current           | 4 A                          |
| Rated voltage           | 50 V                         |
| Rated impulse voltage   | 1.5 kV                       |
| Pollution degree        | 3                            |
| Overvoltage category    | III                          |



Pushing Performance  
Since 1945

## Technical characteristics

|   |                             |
|---|-----------------------------|
| Insulation resistance                     | $>10^8 \Omega$              |
| Contact resistance                        | $\leq 10 \text{ m}\Omega$   |
| Tightening torque                         | 0.6 Nm                      |
| Wrench size (knurled screw / knurled nut) | 17                          |
| Limiting temperature                      | -40 ... +85 °C              |
| Mating cycles                             | $\geq 100$                  |
| Degree of protection acc. to IEC 60529    | IP65 / IP67 mated condition |
| Cable diameter                            | 6 ... 8 mm                  |
| Isolation group                           | I ( $600 \leq \text{CTI}$ ) |

## Material properties

|                                      |  |
|--------------------------------------|--|
| Material (insert)                    | Polyamide (PA)   |
| Material (contacts)                  | Brass  |
| Surface (contacts)                   | Au over Ni Mating side                                 |
| Material (hood/housing)              | Polyamide (PA)<br>Zinc die-cast                        |
| RoHS                                 | compliant with exemption                               |
| RoHS exemptions                      | 6(c): Copper alloy containing up to 4 % lead by weight |
| ELV status                           | compliant with exemption                               |
| China RoHS                           | 50   |
| REACH Annex XVII substances          | Not contained  |
| REACH ANNEX XIV substances           | Not contained  |
| REACH SVHC substances                | Yes  |
| REACH SVHC substances                | Lead   |
| ECHA SCIP number                     | ba9f6f96-3ce5-4eaf-9782-1859ca585f85                   |
| California Proposition 65 substances | Yes  |
| California Proposition 65 substances | Lead<br>Nickel<br>Naphthalene                          |
| Fire protection on railway vehicles  | EN 45545-2 (2020-08)                                   |
| Requirement set with Hazard Levels   | R26  |

## Specifications and approvals

|                |                 |
|----------------|-----------------|
| Specifications | IEC 61076-2-101 |
|----------------|-----------------|



**Pushing Performance**  
Since 1945

## Specifications and approvals

|          |  |
|----------|--|
| UL / CSA | UL 1977 ECBT2.E102079<br>CSA-C22.2 No. 182.3 ECBT8.E102079 |
|----------|--|

## Commercial data

|                                |  |
|--------------------------------|--|
| Packaging size                 | 1  |
| Net weight                     | 39.8 g   |
| Country of origin              | Germany  |
| European customs tariff number | 85366990   |
| GTIN                           | 5713140137455                                    |
| eCl@ss                         | 27440116 Circular connector (for field assembly) |